	acal
Submit 3 Copies To Appropriate District State of New Mexico	Form C-103
Office District I Energy, Minerals and Natural R	esources Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 88240 District II 811 South First Artesia, NM 88210 OIL CONSERVATION DIV	WELL API NO. 30-005-63379
811 South First, Artesia, NM 88210 OIL CONSERVATION DIV District III 1220 South St. Francis I	5 Indiana CI
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505	STATE X FEE
1220 S. St. Francis Dr., Santa Fe, NM 87505	6. State Oil & Gas Lease No. LG-4920
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BA DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUC PROPOSALS.)	
1. Type of Well: Oil Well Gas Well X Other	<u>;</u>
2. Name of Operator	7. Well No.
Yates Petroleum Corporation	#4
3. Address of Operator 105 S. 4 th Street Artesia, NM 88210	8. Pool name or Wildcat Undesignated Foor Ranch
4. Well Location	
Unit Letter <u>E</u> : 1980 feet from the <u>North</u> line and <u>660</u> feet from the <u>West</u> line	
Section 23 Township 98 Range 26	
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3783' GR	
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
	MEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON	MMENCE DRILLING OPNS. X PLUG AND ABANDONMENT
PULLUR ALTER CASING	SING TEST AND MENT JOB
	HER:
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 5/15/01 – Spudded 20" conductor hole at 12:30 PM. Set 40' of 16" conductor pipe, cemented to surface. 5/22/01 – Resumed drilling with rotary tool at 5:00 PM. Notified Phil Hawkins of OCD of operations. 5/24/01 – Reached TD of 12-1/4" surface hole at 1131' a 12:45 PM. Ran 26 joints (1131.45') 8-5/8" 24# J55 casing set at 1131'. Texas pattern guide shoe set at 1131'. Insert float set at 1088.27'. Cemented with 400 sxs 35:65 Poz C with 6% D20 + 2% S1 + .125 pps D130 (yld 1.99, wt 12.6). Tailed in with 200 sxs C + 2% S1 (yld 1.32, wt 14.8). Plug down at 8:00 PM. Bumped plug to 924 psi, held OK. Circ 56 sxs. WOC. 5/24/01 – Drilled out at 9:00 PM. WOC 25 hours. Reduced hole to 7-7/8" and resumed drilling.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE Engineering Technician DATE December 27, 2001 Type or print name Susan/Herpin Telephone No. 505-748-1471	
(This space for State use) ORIGINAL SIGNED BY TIM W. GU	*
APPPROVED BY TITLE Conditions of approval, if any:	JAN 0 7 2002 DATE