			C198	Á
Submit 3 Copies To Appropriate District Office	State of New Mexico			Form C-103
District I 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources		WELL API NO.	Revised March 25, 1999
District II 811 South First, Artesia, NM 88210	OIL CONSERVATION DIVISION		30-005-63388	
District III	1220 South St. Francis Dr.		5. Indicate Type	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		STATE 6. State Oil & G	
1220 S. St. Francis Dr., Santa Fe, NM 87505			LG-8004	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)  1. Type of Well:			7. Lease Name or Unit Agreement Name: State 25 Com	
Oil Well Gas Well X	Other	4		
2. Name of Operator	ration		7. Well No. <b>#2</b>	
Yates Petroleum Corporation  3. Address of Operator 105 S. 4th Street Artesia, NM 88210			8. Pool name or	Wildcat
-	ia, NM 88210 $^{-1}$	RTESIA A	Comanch	e Springs
A 177 11 7		<u></u>	Pre-Permi	an
4. Well Location				
Unit Letter   I : 19	780 feet from the South	line and <b>990</b>	feet from the	iast line
0.5	1. 100 5 0/	F	<b>C</b> I	
Section 25 Township 10S Range 26E NMPM Chaves County  10. Elevation (Show whether DR, RKB, RT, GR, etc.)				
3698' GR				
	ppropriate Box to Indicate N			,
NOTICE OF INTENTION TO: SUB			SEQUENT RE	<del>,,</del>
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WOR	K 🗀	ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS		DMMENCE DRILLING OPNS. PLUG AND ABANDONMENT	
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AI CEMENT JOB	ND	
OTHER:			cement production	
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.  7/15/01 – Reached TD of 6361' at 2:45 AM.  7/16/01 – Run open hole logs.  7/17/01 – Ran 152 joints (6372.7') casing set at 6361' as follows:  46 joints 4-1/2" 11.6# N-80 SB (1924.02')  106 joints 4-1/2" 11.6# N-80 MV (4448.68')  Float shoe set at 6361'. Float collar set at 6317.82'. Bottom marker set at 6309.28'. Top marker set at 4436.98'.  Cemented with 540 sxs Pecos Valley Lite with 1 pps D44 + .2% D65 + .3% D167 + .2% D46 + .15% D  13 + 4 pps D24 (yld 1.42, wt 13).  Plug down at 12:11 PM . Bumped plug to 1600 psi for 2 mins, held OK.  Rig released at 5:15 PM 7/17/01.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE MER TITLE Engineering Technician DATE January 14, 2002				
Type or print name Susan Hel	r <b>pin</b>		Telephone	No. <b>505-748-1471</b>
(This space for State use)	RIGINAL SIGNED BY TIM W. ISTRICT II SUPERVISOR			
APPPROVED BY Conditions of approval, if any:	TITLE_			DATE JAN 28 2002