			~ c15	
Submit 3 Copies To Appropriate District	State of New Mexico		Form C-103	
Office District I	Energy, Minerals and Natural Resources		WELL API NO.	Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 88240				•
District II 811 South First, Artesia, NM 88210 OL CONSERVATION DIVISION		30-005-63390 5. Indicate Type of	of Lease	
District III 1000 Rio Brazos Rd., Aztec, NM 37410	1220 South St. Francis Dr. Santa Fe. NM 87505		STATE X FEE	
District IV 1220 S. St. Francis Dr., Santa Fe, NM			6. State Oil & Gas Lease No.	
87505			LG-7642	
SUNDRY NOTICES AND REPORTS ON WHELS (DO NOT USE THIS FORM FOR PROPOSALS TO DRIVE OR TO DEFINE OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name: Vanilla AZA State	
1. Type of Well: Oil Well Gas Well X	Other 3	A		
2. Name of Operator			7. Well No.	
Yates Petroleum Corpor	ation \checkmark \int_{∞}^{∞}	2002	#1	
3. Address of Operator	RE	CEIVED 🖬	8. Pool name or	
105 S. 4 th Street Artesi	12	ARTESIA 5	Undesignated Foor Ranch Pre-Permian	
4. Well Location				
4. Well Location Unit Letter A : 660 feet from the North line and 990 feet from the East line				
Section 28 Township 9S Range 26E NMPM Chaves County				
10. Elevation (Show whether DR, RKB, RT, GR, etc.)				
3765' GR 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
			SEQUENT RE	
				ALTERING
	PLUG AND ABANDON REMEDIAL WOR			
	CHANGE PLANS		COMMENCE DRILLING OPNS. ABANDONMENT	
		CEMENT JOB		
OTHER:	Clearly state all partin		cement production	
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or				
recompilation. 8/16/01 - Reached TD of 6308' at 3:30 PM.				
8/17/01 – Run open hole logs. Logger's TD 6308'				
8/18/01 – Ran 149 joints (6312.85') casing set at 6308' as follows:				
52 joints 5-1/2" 15.5# SB (2173.59')				
97 joints 5-1/2" 15.5# MV (4139.26') Float shoe set at 6308'. Float collar set at 6263.01'. Bottom marker set at 5268.27'.				
Cemented with 450 sxs Pecos Valley Lite with 1 pps D44 + 4 pps D24 + .2% D65 +.3% D167+ .2% D46 + .15% D167				
(yld 1.42, wt 13). PD at 12:30PM. Bumped plug to 1690 psi for 1 min, held OK.				
Notified Phil Hawkins with OCI				
Rig released at 7:15 PM 8/18/0	51.			
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Augen Augen TITLE Engineering Technician DATE December 31, 2001				
SIGNATURE Altan All	pre	Engineering Tec	hnician_DATE	<u>December 31, 2001</u>
Type or print name Susan Herpin Telephone No. 505-748-1471				
(This space for State se)	WAL SIGNED BY TIM W. GI			
APPPROVED BY	TOTLE			D.LAN 0 7 2002
Conditions of approval, if any:				

...