Form 3180-5 (August 1999)

TED STATES DEPAR NT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135

Expires November 30, 2000 5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS	
Do not use this form for proposals to drill or to re-ente	>
to proposals to drill or to re-ente	

abandoned well. Use Form 3160-3 (APD) for such proposals.

M-11592
If Indian, Allottee or Tripe Name
if Unit or CA/Agreement, Name and/or No.

SUBMI	T IN TRIPLICATE -	Other Instructions		7. If Unit or CA/Agreement, Name and/or No
·· · Abe of Ageil		- Instructions	on reverse side	
Oil Well	X Gas Well	Other		8. Well Name and No.
2. Name of Operator			14.252	Gyp MO Federal Com #2
Yates Petroleum C 3a Address	Corporation /		.	9. API Well No.
105 S. 4th Street -	Artesia NM Bondo	3b. Phone No. (incl.	ude area code)	2 30-005-63399
Location of Well (Footage, Se	ec., T.,R., M., or Survey Desc	505-748-1471		10. Field and Pool, or Exploratory Area
000 LMC and 1880, FET	,		OCD RECEIVED	ω Wildcat Precambrian
Section 35, T5S R24E			OCD - ARTESIA	11. County or Parish, State
12. CHECK A	PPROPRIATE BOYE	0) =0	- ¹ 2	Chaves Court and
YPE OF SUMISSION	THOPKIATE BUX(E	S) TO INDICATE NAT	URE OF MOTICE REPOR	Chaves County, NM 1. OR OTHER DATA
Notice of Intent	Acidize		TYPE OF ACTION	
Subsequent Report		Deepen	Froduction (Start/Resume)	Water Shut-Off
	Alter Casing	Fracture Treat	Reclamation	Well Integrity
Final Abandonment Notice	Casing Repair	New Construction	Recomplete	
ļ	Change Plans	Plug and Abandon		X Other Commence Drilling
	Convert to Injection		Temporarily Abandon	
. Describe Proposed or Completed (Operation (almost	Plug Back	Water Disposal	roximate duration thereof. If the proposal is to deepen
reclamation, have been completed. 7/20/01 - Spudded 20" con 7/29/01 - Resumed drilling 7/30/01 - Reached TD of si	and the operator has determined inductor hole at 11:30 AM. with rotary tools, 14-3/4"	that the site is ready for final ins Set 40' of 16" conducto hole.	ays following completion of the involved on inpleted. Final Abandonment Notices shall specition.) If pipe, cemented to surface.	perations. If the operations results in a multiple lbe filed only after all requirements, including
redamation, have been completed, 7/20/01 - Spudded 20" con 7/29/01 - Resumed drilling 7/30/01 - Reached TD of siset at 918'. Texas Pattern polyflake and 400 sxs C 35	and the operator has determined inductor hole at 11:30 AM. with rotary tools, 14-3/4" surface hole at 3:45 PM at guide shoe set at 918'. 15:65:6 + 2% CaCl2 + 1/8 p	s med once testing has been contract that the site is ready for final ins Set 40' of 16" conducto hole. 1918'. Ran 21 joints (90-insert float set at 878.79' ops polyflake (yld 1.99, war 700#, held OK. WOC. Siced hole to 11" and resured to 11" and resured hole.	ays following completion of the involved on pieted. Final Abandonment Notices shall precition.) If pipe, cemented to surface. 4.78' + 16.11' landing joint and surface. Cemented with 150 sxs 35.65 of 12.6). Tailed in with 200 sxs stan Mayo with BLM witnessed jumed drilling. TED FOR RECORD.	perations. If the operations results in a multiple libe filed only after all requirements, including shoe) 11-3/4" 42# HE casing,
reclamation, have been completed, 7/20/01 - Spudded 20" con 7/29/01 - Resumed drilling 7/30/01 - Reached TD of siset at 918'. Texas Pattern polyflake and 400 sxs C 35 7/31/01 - Plug down at 12:3 Drilled out at 7:30 PM. WC	and the operator has determined nductor hole at 11:30 AM. with rotary tools, 14-3/4" surface hole at 3:45 PM at guide shoe set at 918'. I 5:65:6 + 2% CaCl2 + 1/8 g 30 AM. Bumped plug to 70 CC 19 hrs 30 mins. Redu	s med once testing has been continuated by the site is ready for final instance of the site is ready for final instance of the site is ready for site is ready for the site is ready for final instance of the site is ready for site is ready	ays following completion of the involved on inpleted. Final Abandonment Notices shall specifion.) If pipe, cemented to surface. 4.78' + 16.11' landing joint and surface with 150 sxs 35:65 at 12.6). Tailed in with 200 sxs at 12.6	perations. If the operations results in a multiple libe filed only after all requirements, including shoe) 11-3/4" 42# HE casing,
reclamation, have been completed. 7/20/01 - Spudded 20" con 7/29/01 - Resumed drilling 7/30/01 - Reached TD of si set at 918'. Texas Pattern polyflake and 400 sxs C 35 7/31/01 - Plug down at 12:3 Drilled out at 7:30 PM. WO	and the operator has determined nductor hole at 11:30 AM. with rotary tools, 14-3/4" surface hole at 3:45 PM at guide shoe set at 918'. I 5:65:6 + 2% CaCl2 + 1/8 g 30 AM. Bumped plug to 70 CC 19 hrs 30 mins. Redu	s med once testing has been continuated by the site is ready for final instance of the site is ready for final instance of the site is ready for site is ready for the site is ready for final instance of the site is ready for site is ready	ays following completion of the involved on pieted. Final Abandonment Notices shall precition.) In pipe, cemented to surface. 4.78' + 16.11' landing joint and surface. Cemented with 150 sxs 35:65 of 12.6). Tailed in with 200 sxs of 12.6). Tailed in with 200 sxs of 12.6. Tailed in wi	perations. If the operations results in a multiple libe filed only after all requirements, including shoe) 11-3/4" 42# HE casing,
reclamation, have been completed, 7/20/01 - Spudded 20" con 7/29/01 - Resumed drilling 7/30/01 - Reached TD of siset at 918'. Texas Pattern polyflake and 400 sxs C 35 7/31/01 - Plug down at 12:3 Drilled out at 7:30 PM. WO	and the operator has determined nductor hole at 11:30 AM. with rotary tools, 14-3/4" surface hole at 3:45 PM at guide shoe set at 918'. I 5:65:6 + 2% CaCl2 + 1/8 g 30 AM. Bumped plug to 70 CC 19 hrs 30 mins. Redu	s med once testing has been continuated by the site is ready for final instance of the site is ready for final instance of the site is ready for site is ready for the site is ready for final instance of the site is ready for site is ready	ays following completion of the involved on pieted. Final Abandonment Notices shall precition.) If pipe, cemented to surface. 4.78' + 16.11' landing joint and surface. Cemented with 150 sxs 35:65 of 12.6). Tailed in with 200 sxs stan Mayo with BLM witnessed jumed drifting. TED FOR RECORD ANDC A. LOPEZ DLEUM ENGINEER	perations. If the operations results in a multiple of the filed only after all requirements, including shoe) 11-3/4" 42# HE casing, 1:6 C + 5 pps gilsonite + 1/8 pps Class C + 2% CaCl2 (yld 1.32, wt 14.8). iob.
reclamation, have been completed. 7/20/01 - Spudded 20" con 7/29/01 - Resumed drilling 7/30/01 - Reached TD of si set at 918'. Texas Pattern polyflake and 400 sxs C 35 7/31/01 - Plug down at 12:3 Drilled out at 7:30 PM. WO	and the operator has determined aductor hole at 11:30 AM. with rotary tools, 14-3/4" surface hole at 3:45 PM at guide shoe set at 918'. I 5:65:6 + 2% CaCl2 + 1/8 p 30 AM. Bumped plug to 70 DC 19 hrs 30 mins. Redu	s med once testing has been continuated by the site is ready for final instance of the site is ready for final instance of the site is ready for site is ready for the site is ready for final instance of the site is ready for site is ready	ays following completion of the involved on pieted. Final Abandonment Notices shall precition.) In pipe, cemented to surface. 4.78' + 16.11' landing joint and surface. 4.78' + 16.11' landing joi	perations. If the operations results in a multiple of the filed only after all requirements, including shoe) 11-3/4" 42# HE casing, i.6 C + 5 pps gilsonite + 1/8 pps Class C + 2% CaCl2 (yld 1.32, wt 14.8), i.6 c.
reclamation, have been completed. 7/20/01 - Spudded 20" con 7/29/01 - Resumed drilling 7/30/01 - Reached TD of si set at 918'. Texas Pattern polyflake and 400 sxs C 35 7/31/01 - Plug down at 12:3 Drilled out at 7:30 PM. WO	and the operator has determined inductor hole at 11:30 AM. with rotary tools, 14-3/4" surface hole at 3:45 PM at guide shoe set at 918'. I 5:65:6 + 2% CaCl2 + 1/8 p 30 AM. Bumped plug to 70°C 19 hrs 30 mins. Reductive and correct	s med once testing has been contributed the site is ready for final insight of the site is ready for the sit	ays following completion of the involved on pieted. Final Abandonment Notices shall precition.) If pipe, cemented to surface. 4.78' + 16.11' landing joint and sometime of the complete of t	perations. If the operations results in a multiple of the filed only after all requirements, including shoe) 11-3/4" 42# HE casing, i.6 C + 5 pps gilsonite + 1/8 pps Class C + 2% CaCl2 (yld 1.32, wt 14.8). i.6 b.
reclamation, have been completed. 7/20/01 - Spudded 20" con 7/29/01 - Resumed drilling 7/30/01 - Reached TD of si set at 918'. Texas Pattern polyflake and 400 sxs C 35 7/31/01 - Plug down at 12:: Drilled out at 7:30 PM. WC	and the operator has determined inductor hole at 11:30 AM. with rotary tools, 14-3/4" surface hole at 3:45 PM at guide shoe set at 918'. I 5:65:6 + 2% CaCl2 + 1/8 p 30 AM. Bumped plug to 70°C 19 hrs 30 mins. Reductive and correct	s med once testing has been contributed the site is ready for final insight of the site is ready for the sit	ays following completion of the involved on pieted. Final Abandonment Notices shall precition.) If pipe, cemented to surface. 4.78' + 16.11' landing joint and sometime of the complete of t	perations. If the operations results in a multiple of the filed only after all requirements, including shoe) 11-3/4" 42# HE casing, i.6 C + 5 pps gilsonite + 1/8 pps Class C + 2% CaCl2 (yld 1.32, wt 14.8). i.6 b.
reclamation, have been completed, 7/20/01 - Spudded 20" con 7/29/01 - Resumed drilling 7/30/01 - Reached TD of siset at 918'. Texas Pattern polyflake and 400 sxs C 35 7/31/01 - Plug down at 12:3 Drilled out at 7:30 PM. WC	and the operator has determined inductor hole at 11:30 AM. with rotary tools, 14-3/4" surface hole at 3:45 PM at guide shoe set at 918'. I 5:65:6 + 2% CaCl2 + 1/8 p 30 AM. Bumped plug to 70°C 19 hrs 30 mins. Reductive and correct	s med once testing has been contributed the site is ready for final insight of the site is ready for the sit	ays following completion of the involved on pieted. Final Abandonment Notices shall precition.) In pipe, cemented to surface. 4.78' + 16.11' landing joint and surface. 4.78' + 16.11' landing joi	perations. If the operations results in a multiple of the filed only after all requirements, including only a
Thereby certify that the foregoing is to Name (Printed/Typed) Susan Herpin Signature Approved by T/20/01 - Spudded 20" con 7/29/01 - Resumed drilling 7/30/01 - Reached TD of signature 400 sxs C 35 7/31/01 - Plug down at 12:: Drilled out at 7:30 PM. WC Susan Herpin Signature	and the operator has determined nductor hole at 11:30 AM. with rotary tools, 14-3/4" surface hole at 3:45 PM at guide shoe set at 918'. I 5:65:6 + 2% CaCl2 + 1/8 p 30 AM. Bumped plug to 70 DC 19 hrs 30 mins. Redu	PACE FOR FEDER	ays following completion of the involved on pieted. Final Abandonment Notices shall precition.) In pipe, cemented to surface. 4.78' + 16.11' landing joint and sometimes. Cemented with 150 sxs 35:65 at 12.6). Tailed in with 200 sxs of 12.6). Tailed in with 200 sxs of 12.6. Tailed in	perations. If the operations results in a multiple of the filed only after all requirements, including shoe) 11-3/4" 42# HE casing, i.6 C + 5 pps gilsonite + 1/8 pps Class C + 2% CaCl2 (yld 1.32, wt 14.8). i.6 b.
Thereby certify that the foregoing is to Name (Printed/Typed) Susan Herpin Figoration, have been completed. 7/20/01 - Spudded 20" con 7/29/01 - Resumed drilling 7/30/01 - Reached TD of siset at 918'. Texas Pattern polyflake and 400 sxs C 35 7/31/01 - Plug down at 12:: Drilled out at 7:30 PM. WO	and the operator has determined and uctor hole at 11:30 AM. with rotary tools, 14-3/4" surface hole at 3:45 PM at guide shoe set at 918'. I 5:65:6 + 2% CaCl2 + 1/8 p 30 AM. Bumped plug to 70 DC 19 hrs 30 mins. Redu	PACE FOR FEDER	ays following completion of the involved on pieted. Final Abandonment Notices shall precition.) In pipe, cemented to surface. 4.78' + 16.11' landing joint and sometimes. Cemented with 150 sxs 35:65 at 12.6). Tailed in with 200 sxs of 12.6). Tailed in with 200 sxs of 12.6. Tailed in	perations. If the operations results in a multiple performed sperations. If the operations results in a multiple of the filed only after all requirements, including shoe) 11-3/4" 42# HE casing, ci6 C + 5 pps gilsonite + 1/8 pps Class C + 2% CaCl2 (yld 1.32, wt 14.8). iob.