Form 31	60-5
(August	1999)

DEPART IT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

. Co NM DIV-	FORM APPROVED NS. OMB No 1004-0135 Dist. 2Expires November 30, 2000	CISF
1301 W. Gran Artesia, NN	I C PAVEFICE	

SUNDRY NOTICES AND REPORTS ON WELLS	
-------------------------------------	--

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (AFD) for such proposals.

				 If Unit or CA/Agreement, Name and/or No
SUBMIT	IN TRIPLICATE - C	ther Instructions	on reverse side	
Type of Well Oil Well	X Gas Well	Other	635-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	8. Well Name and No. Five Mile Draw LX Federal Com #2
Name of Operator Yates Petroleum Co	prporation			9. API Well No. 30-005-63401
Address 105 S. 4th Street - A		3b. Phone No. (inclue 505-748-1471	de area code) DECENCED	10. Field and Pool, or Exploratory Area
Location of Well (Footage, Se				Pecos Slope Abo
000' FSL and 1000' FWL			OCD - ARTEST	11. County or Parish, State
ection 34, T6S-R25E			C. C	· ·
				Chaves County, NM
and the second	PPROPRIATE BOX(ES	S) TO INDICATE NAT	URE OF NUTUE, AEFORT,	OR OTHER DATA
YPE OF SUMISSION			TYPE OF ACTION	
Notice of Intent	Acidize	Deepen	Production (Start/Resume)	Water Shut-Off
Subsequent Report	Alter Casing	Fracture Treat	Reclamation	Well Integrity
Final Abandonment Notice	Casing Repair	New Construction	Recomplete	X Other Set and cement
	Change Plans	Plug and Abandon	Temporarily Abandon	intermediate casing
	Convert to injection	Plug Back	Water Disposal	
completion or recompletion in a ne reclamation, have been completed 8/4/01 - Reached TD of 1 Ran 36 joints (1559.77') 8	h BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b d, and the operator has determined 1" hole at 1560' at 6:00 A J-5/8" 24# J-55 casing set	e filed once testing has been co d that the site is ready for final in M. at 1560'. Texas pattern	tays following completion of the involved or mpleted. Final Abandonment Notices shall specifion.) guide shoe set at 1560'. Insert	ttach the Bond under which the work will be performed berations. If the operations results in a multiple be filed only after all requirements, including float set at 1519.96'.
completion or recompletion in a ne reclamation, have been completed 8/4/01 - Reached TD of 1 Ran 36 joints (1559.77') 8	h BLM/BIA. Required subsequent an interval, a Form 3160-4 shall b d, and the operator has determined 1" hole at 1560' at 6:00 A I-5/8" 24# J-55 casing set class C + 2% CaCl2 (yld 1	e filed once testing has been co d that the site is ready for final in M. at 1560'. Texas pattern .32, wt 14.8). Plug dowr	tays following completion of the involved op mpleted. Final Abandonment Notices shall specifion.) guide shoe set at 1560'. Insert n at 2:45 PM. Bumped plug to 8:	perations. If the operations results in a multiple be filed only after all requirements, including float set at 1519.96'.
completion or recompletion in a ne reclamation, have been completed 8/4/01 - Reached TD of 1 Ran 36 joints (1559.77') 8 Cemented with 260 sxs C 8/5/01 - Drilled out at 9:00	h BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b d, and the operator has determined 1" hole at 1560' at 6:00 A J-5/8" 24# J-55 casing set class C + 2% CaCl2 (yld 1 0 AM. Reduced hole to 7-	e filed once testing has been co d that the site is ready for final in M. at 1560'. Texas pattern .32, wt 14.8). Plug dowr	tays following completion of the involved op mpleted. Final Abandonment Notices shall specifion.) guide shoe set at 1560'. Insert n at 2:45 PM. Bumped plug to 8:	berations. If the operations results in a multiple be filed only after all requirements, including float set at 1519.96'. 33 psi, held OK. WOC. ACCEPTED FOR RECORD
completion or recompletion in a nereclamation, have been completed 8/4/01 - Reached TD of 1 Ran 36 joints (1559.77') 8 Cemented with 260 sxs C 8/5/01 - Drilled out at 9:00	h BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b d, and the operator has determined 1" hole at 1560' at 6:00 A J-5/8" 24# J-55 casing set class C + 2% CaCl2 (yld 1 0 AM. Reduced hole to 7-	e filed once testing has been co d that the site is ready for final in M. at 1560'. Texas pattern .32, wt 14.8). Plug dowr	tays following completion of the involved op mpleted. Final Abandonment Notices shall specifion.) guide shoe set at 1560'. Insert n at 2:45 PM. Bumped plug to 8:	berations. If the operations results in a multiple be filed only after all requirements, including float set at 1519.96'. 33 psi, held OK. WOC. ACCEPTED FOR RECORD
completion or recompletion in a nereclamation, have been completed 8/4/01 - Reached TD of 1 Ran 36 joints (1559.77') 8 Cemented with 260 sxs C 8/5/01 - Drilled out at 9:00 I hereby certify that the foregoing Name (Panted/Typed)	h BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b d, and the operator has determined 1" hole at 1560' at 6:00 A J-5/8" 24# J-55 casing set class C + 2% CaCl2 (yld 1 0 AM. Reduced hole to 7-	e filed once testing has been co d that the site is ready for final in M. at 1560'. Texas pattern .32, wt 14.8). Plug dowr	tays following completion of the involved of mpleted. Final Abandonment Notices shall specifion.) guide shoe set at 1560'. Insert n at 2:45 PM. Bumped plug to 8: g.	berations. If the operations results in a multiple be filed only after all requirements, including float set at 1519.96'. 33 psi, held OK. WOC. ACCEPTED FOR RECORD FEB 2 5 2002 FEB 2 5 20
completion or recompletion in a nere reclamation, have been completed 8/4/01 - Reached TD of 1 Ran 36 joints (1559.77') 8 Cemented with 260 sxs C 8/5/01 - Drilled out at 9:00	h BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b d, and the operator has determined 1" hole at 1560' at 6:00 A J-5/8" 24# J-55 casing set class C + 2% CaCl2 (yld 1 0 AM. Reduced hole to 7-	e filed once testing has been co d that the site is ready for final in M. at 1560'. Texas pattern .32, wt 14.8). Plug dowr	tays following completion of the involved of mpleted. Final Abandonment Notices shall specifion.) guide shoe set at 1560'. Insert in at 2:45 PM. Bumped plug to 8 g. Title Engineering Techni Date	berations. If the operations results in a multiple be filed only after all requirements, including float set at 1519.96'. 33 psi, held OK. WOC. ACCEPTED FOR RECORD FEB 2 5 2002 FEB 2 5 20
completion or recompletion in a nere reclamation, have been completed 8/4/01 - Reached TD of 1 Ran 36 joints (1559.77') 8 Cemented with 260 sxs C 8/5/01 - Drilled out at 9:00 I hereby certify that the foregoing Name (<i>Panted/Typed</i>) Susan Herpin	h BLM/BIA. Required subsequent winterval. a Form 3160-4 shall b t, and the operator has determined 1" hole at 1560' at 6:00 A I-5/8" 24# J-55 casing set lass C + 2% CaCl2 (yld 1 0 AM. Reduced hole to 7-	e filed once testing has been co d that the site is ready for final in M. at 1560'. Texas pattern .32, wt 14.8). Plug dowr 7/8" and resumed drilling	tays following completion of the involved of mpleted. Final Abandonment Notices shall specifion.) guide shoe set at 1560'. Insert in at 2:45 PM. Bumped plug to 8 g. Title	berations. If the operations results in a multiple be filed only after all requirements, including float set at 1519.96'. 33 psi, held OK. WOC. ACCEPTED FOR RECORD FEB 2 5 2002 FEB 2 5 2002 ACCEPTED FOR RECORD FEB 2 5 2002 ACCEPTED FOR RECORD
completion or recompletion in a nereclamation, have been completed 8/4/01 - Reached TD of 1 Ran 36 joints (1559.77') 8 Cemented with 260 sxs C 8/5/01 - Drilled out at 9:00 I hereby certify that the foregoing Name (<i>Printed/Typed</i>) Susan Herpin	h BLM/BIA. Required subsequent winterval. a Form 3160-4 shall b t, and the operator has determined 1" hole at 1560' at 6:00 A I-5/8" 24# J-55 casing set lass C + 2% CaCl2 (yld 1 0 AM. Reduced hole to 7-	e filed once testing has been co d that the site is ready for final in M. at 1560'. Texas pattern .32, wt 14.8). Plug dowr 7/8" and resumed drilling	tays following completion of the involved op mpleted. Final Abandonment Notices shall specifion.) guide shoe set at 1560'. Insert in at 2:45 PM. Bumped plug to 8 g. Title Engineering Techni Date	berations. If the operations results in a multiple be filed only after all requirements, including float set at 1519.96'. 33 psi, held OK. WOC. ACCEPTED FOR RECORD FEB 2 5 2002 FEB 2 5 2002 ACCEPTED FOR RECORD FEB 2 5 2002 ACCEPTED FOR RECORD

or fraudulent statements or representations as to any matter within its jurisdiction



2002 FEB 14 AM 8: 41

