				LISPAD	
Submit 3 Copies To Appropriate District Office <u>District I</u>	State of New M Energy, Minerals and Nat		Form C-103 Revised March 25, 1999 WELL API NO.		
1625 N. French Dr., Hobbs, NM 88240 District II	OIL CONSERVATION	NDIVISION	30-005-63418		
811 South First, Artesia, NM 88210 District III		1220 South St. Francis Dr.		5. Indicate Type of Lease	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		STATE X FEE 6. State Oil & Gas Lease No.		
1220 S. St. Francis Dr., Santa Fe, NM 87505			LG-0563		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well X Other			7. Lease Name or Unit Agreement Name: Smernoff NL St.		
2. Name of Operator			7. Well No.		
Yates Petroleum Corporation			8. Pool name or Wildcat		
3. Address of Operator 105 S. 4 th Street Artesia, NM 88210			Pecos Slope Abo		
4. Well Location				······································	
Unit Letter <u>H : 19</u>	80 feet from the <u>North</u> 1	ine and 660 fo	eet from the East	line	
Section 2	Township 5S Range		NMPM Chav	es County	
	10. Elevation (Show whether 1 393	B' GR	<i>(C.)</i>		
11. Check A	ppropriate Box to Indicate N		, Report or Other 1	Data	
NOTICE OF IN		SUE	BSEQUENT REI	PORT OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WO	RK 🗍	ALTERING CASING	
	CHANGE PLANS		RILLING OPNS. X	PLUG AND ABANDONMENT	
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST A CEMENT JOB			
OTHER:		OTHER:			
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 9/10/01 – Spudded conductor hole at 9:30 AM. Set and cemented 40' of 16'' conductor pipe. Notified Phil Hawkins with OCD of spud. 9/20/01 – Resumed drilling at 2:00 AM with rotary tools. 9/21/01 – Reached TD of 14-3/4'' hole at 906' at 12:45 PM. Ran 20 joints (906.85') 11-3/4'' 42# HE casing set at 906'. Texas Pattern guide shoe set at 906'. Insert float set at 862.03'. Cemented with 450 sxs 35:65:6 C + 2% CaCl2 + 5 pps gilsonite (yld 1.99, wt 12.6). Tailed in with 200 sxs C + 2% CaCl2 (yld 1.32, wt 14.8). Plug down at 7:30 PM. Circ 58 sxs. WOC. 9/22/01 – Drilled out at 2:45 PM. WOC 19 hrs. 15 mins. Reduced hole to 11'' and resumed drilling. 9/24/01 – Drilled to 1526'. Displace hole with 10# brine, no fluid loss. Reduced hole to 7-7/8'' and resumed drilling.					
I hereby certify that the information	above is true and complete to the	e best of my knowle	edge and belief.		
SIGNATURE ALTER CALL	pin	Engineering Tea	chnician DATE	December 18, 2001	
Type or print name Susan He	rpin		Telephone	No. 505-748-1471	
(This space for State use)					
APPPROVED BY Conditions of approval, if any:	Record			DATE	
constraints of approval, it and	N N				

APPPROVED BY	
Conditions of approval.	if