	-			168
Submit 3 Copies To Appropriate District Office State of New Mexico			<i>c</i>	Form C-103
District!	Energy, Minerals and Natural Resources		WELL API NO.	Reased March 25, 1999
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u>	OIL CONSERVATION DIVISION		30-005-63419	1
NI South Phys. Anesia, NM 88210 OH, CONSERVATION DIVISION District III 1220 South St. Francis Dr.		5. Indicate Type of	of Lease	
District IV Santa Fe. Nivi 87505		STATE [		
1220 S. St. Francis Dr., Santa Fe, NM 87505			LG-0563	us Lease 140.
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or	Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			Smernoff NL State	
PROPOSALS.)  1. Type of Well:			Smemon ML S	idle
Oil Well Gas Well X	Other	4		
2. Name of Operator			7. Well No.	
Yates Petroleum Corporation #6  3. Address of Operator 8. Pool name or Wildcat				
105 S. 4th Street Artesia, NM 88210			Pecos Slope Abo	
4. Well Location				
4. Well Location				
Unit Letter L: 1980 feet from the South line and 1190 feet from the West line				
Section 2	Township <b>5S</b> Rar	nge <b>24E</b> 1	NMPM <b>Chav</b>	es County
Section 2	10. Elevation (Show whether			es County
3956' GR				
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
			SEQUENT REI	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WOR		ALTERING CASING D
TEMPORARILY ABANDON	CHANGE PLANS		ILLING OPNS. X	ABANDONMENT
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST A CEMENT JOB	עא	
OTHER:				
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of				
starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.				
11/21/01 – Spudded 20" conductor hole at 10:00 AM. Set 40' of 16" conductor pipe, cemented to surface.				
Notified Jerry Guy with OCD of spud. 11/23/01 – Resumed drilling with rotary tools at 5:30 PM.				
11/23/01 – Resumed arilling w 11/24/01 – Reached TD of 14-				
Ran 21 joints (902.93') 11-3/4" 42# HE casing set at 903'. Texas Pattern guide shoe set at 903'. Insert float set at				
860.68'. Cemented with 500 sxs 35:65:6 C + 2% CaCl2 + 5 pps gilsonite + 1/8 pps polyflake (yld 1.99, wt 12.6).				
Tailed in with 200 sxs C + 2% CaCl2 (yld 1.32, wt 14.8). Plug down at 12:30 AM. Bumped plug to 970#, held OK.				
Circ 65 sxs. WOC. Notified Mike Stubblefield with OCD before starting pipe. 11/25/01 – Drilled out at 8:00 PM. WOC 19 hrs 30 mins. Reduced hole to 11" and resumed drilling.				
11/25/01 - Diffied out at 6.001 11/26/01 - Reached TD of 11"			i dia resorrica e	ariming.
See Attached				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE SIGNATURE	TITLE _	Engineering Tec	<b>hnician</b> DATE <u></u>	December 20, 2001
Type or print name Susan He	r <b>pin</b>		Telephone	No. <b>505-748-1471</b>
(This space for State use)	AL SIGNED BY TIM W. GU			NEC 9 a new
APPPROVED BY Conditions of approval, if any:	T II SUPERVISOR TITI			DEC 2 8 2001 DATE