					4
Submit 3 Copies To Appropriate District	State of New Mexico			- CN	Form C-103
Office District I	Energy, Minerals and Natural Resources				Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 88240				WELL API NO.	V I
<u>District II</u> 811 South First, Artesia, NM 88210	OIL CONSERVATION DIVISION			30-005-63429 5. Indicate Type of	flance
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.			STATE	FEE X
District IV	Santa Fe, NM 87505			6. State Oil & G	
1220 S. St. Francis Dr., Santa Fe, NM 87505					
	CES AND REPORTS O			7. Lease Name or	Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			Dubu to ATV		
PROPOSALS.)				Ruby Jo ATY	
1. Type of Well: Oil Well Gas Well X	Other		*		
2. Name of Operator				7. Well No.	
Yates Petroleum Corpor	ation			#3	
3. Address of Operator				8. Pool name or	
105 S. 4 th Street Artesi	ia, NM 88210			Wildcat Pre	ecambrian
4. Well Location		·			
4. Wen Elocation					N I
Unit Letter L: 1880 feet from the South line and 660 feet from the West line					
Section 14	Township 8S	Range	26E NI	MPM Chave	s County
	10. Elevation (Show		R, RKB, RT, GR, e	rc.)	
3890' GR					
	ppropriate Box to Ir	ndicate N			
NOTICE OF IN	TENTION TO:		SUE	BSEQUENT REI	ALTERING
	PLUG AND ABANDO	N	REMEDIAL WOR	кк 🗌	CASING
	CHANGE PLANS			RILLING OPNS. X	PLUG AND ABANDONMENT
PULL OR ALTER CASING	MULTIPLE COMPLETION		CASING TEST A	ND	
OTHER:			OTHER:		
Describe proposed or completed or					
starting any proposed work). SEE I	RULE 1103. For Multip	ple Comple	tions: Attach well	bore diagram of prop	osed completion or
recompilation. 12/28/01 – Spud 20" hole with	ratholo machino a	+ 10.00 AN	A Sot 40° of 14°	conductor nine	component to
surface. Notified Van Barton		1 10.00 AN	7. Sel 40 01 18	conductor pipe	Cemenieu io
1/7/02 – Resumed drilling with 12-1/4" hole with rotary tools at 10:30 AM.					
1/8/02 – Reached TD of surface hole at 1002'. Ran 24 joints (1002.77') 8-5/8" 24# casing set at 1002'. Texas					
pattern guide shoe set at 1002'. Insert float set at 957.24'. Cemented with 500 sxs 35:65 Poz C with 6% D20 + 5					
pps D24 + 2% S1 + .125% D130 (yld 1.99, wt 12.6). Tailed in with 200 sxs C with 2% S1 (yld 1.32, wt 14.8). PD at 2:45					
PM. Bumped plug to 550#, held OK. Circ 79 sxs. WOC. Notified Van Barton with OCD . 1/9/02 – Drilled out at 10:00 AM. WOC 19 hours, 15 mins. Reduced hole to 7-7/8'' and resumed drilling.					
177/02 - Dhiled out at 10.00 AM. WOC 17 hours, 13 mins. Reduced hole 107-776, and resumed aniling.					
I hereby certify that the information	above is true and com	plete to the	best of my knowle	dge and belief.	
SIGNATURE	pin_TIT	TLE <u>E</u>	ngineering Tec	:hnician _DATE_	January 17, 2002

Type or print name Suggn/Herpin	Telephone No. 505-748-1471	
(This space for State used ORIGINAL SHEWED BY THE W. CUR DISTRICT II SUPERVISOR	JAN 3 0 2002 Date	

APPPROVED BY v Conditions of approval, if any: