

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87414
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
RECEIVED
1226 South St. Francis Dr.
Santa Fe, NM 87505
OCD - ARTESIA

Form C-103
Revised March 25, 1999

WELL API NO.

30-005-63432

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Sacra SA

7. Well No.

#21

8. Pool name or Wildcat

Cottonwood Ranch Penn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter L : 1980 feet from the South line and 660 feet from the West line

Section 35 Township 6S Range 25E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3699' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1/26/02 - Spud with rathole machine at 10:00 AM. Set 40' of 16" conductor pipe, cemented to surface. Notified Van Barton with OCD of spud.

1/29/02 - Resumed drilling with rotary tools, 14-3/4" hole, at 9:00 AM.

1/30/02 - Reached TD of surface hole at 910' at 9:15 AM.

Ran 21 joints (910.94') 11-3/4" 42# H-40 casing set at 910'. Texas pattern guide shoe set at 906'. Insert float set at 862.94'. Cemented with 400 sxs 35:65 Poz C with 6% D20 bentonite +2% CaCl2 + 5 pps D24 + .125 pps polyflake (yld 1.99, wt 12.6). Tailed in with 200 sxs C + 2% CaCl2 (yld 1.32, wt 14.8). PD at 4:00 PM. Bumped plug to 750 psi, held OK. Circ 83 sxs. WOC.

1/31/02 - Drilled out at 2:30 PM. WOC 22.5 hours. Reduced hole to 11" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Susan Herpin TITLE Engineering Technician DATE February 5, 2002

Type or print name Susan Herpin

Telephone No. 505-748-1471

(This space for State use)

APPROVED BY TIM W. GUM DISTRICT II SUPERVISOR TITLE

DATE

Conditions of approval, if any:

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

FEB 07 2002