	, 		CIST	
Submit 3 Copies To Appropriate District Cffice District I Energy, Minerals and Natural Resources		WELL API NO.	Form C-103 Revised March 25, 1999	
1625 N. French Dr., Hobbs, NM 88240 District II 211 South First Artesia NM 88210 OIL CONSERVATION DIVISION			30-005-63434	
District III 1220 South St. Francis Dr.		5. Indicate Type of STATE		
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> Santa Fe, NM 87505		STATE X FEE 6. State Oil & Gas Lease No.		
1220 S. St. Francis Dr., Santa Fe, NM 87505			VO-5659	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name: Canner AUF State Com	
1. Type of Well: Oil Well Gas Well X Other				
2. Name of Operator			8. Well No.	
Yates Petroleum Corporation 3. Address of Operator RECURSIA			9. Pool name or Wildcat	
3. Address of Operator 105 S. 4th Street Artesia, NM 88210			Wildcat Precambrian	
4. Well Location				
Unit Letter <u>C: 660</u>) feet from the North lin	ne and <u>1980</u>	feet from the	est line
Section 30	Township 10S Range			aves County
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3718' GR				
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WOR	RK 🗌	ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DR		PLUG AND ABANDONMENT
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB		
OTHER:		OTHER: Set production casing		
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 12/1/02 – Reached ID 6500' at 8:30 PM.				
12/3/02 – Ran 152 joints 5-1/2" 15.5# J-55 casing set at 6500' as follows: 56 joints SB (2374.43'), 96 joints MV (4128.89'). Float shoe set at 6500'. Float collar set at 6457'. Bottom marker set at 5313'. Top marker set at 4126'. Cemented with 470 sx PVL + additives (yld 1.41, wt 13). Maintained circulation throughout job. Notified Jerry Guy with OCD of operations 12/2/02.				
			٠	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Jina Huerta TITLE Regulatory Compliance Supervisor DATE December 13, 2002				
Type or print name Find Huert	·a		Telephone No	505-748-1471
(This space for State 169)	ORIGINAL SIGNED BY T	im W. Gum		DEC 8 7 2002
APPPROVED BY Conditions of approval, if any:	DISTRICT H SUPERYING	R		DATE