_		357-	
Summit 3 Copies To Appropriate District	State of New Mexico	Form C-1	03
Office District I Energy, Minerals and Natural Resources		Revised March 25, 15	999
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.	
District II 811 South First, Artesia, NM 88210 OIL CONSERVATION DIVISION		N 30-005-63446	
District III 1220 South St. Francis Dr.		5. Indicate Type of Lease STATE X FEE	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505		6. State Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM		LG-2622	
87505 SUNDRY NOTICES AND 1	REPORTS ON WELLS	7. Lease Name or Unit Agreement Nam	ne:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRI DIFFERENT RESERVOIR. USE "APPLICATION FOR PROPOSALS.)	LL OR TO DEEPEN OR PLUG BACK TO		
1. Type of Well: Oil Well Gas Well X Other	2021222		
2. Name of Operator	1313	7. Well No.	
Yates Petroleum Corporation		र हैं। #3	
3. Address of Operator		18. Pool name or Wildcat	
105 S. 4 th Street Artesia, NM 8	3210 \(\frac{4}{2}\) \(\frac{7}{2}\) \(\frac{7}\) \(\frac{7}{2}\) \(\frac{7}{2	Wildcat Basement	
4. Well Location	12 ES/10	\$ /	
Unit Letter J : 1980 fe	et from the South Coline and	1980 feet from the East line	
Section 36 Township	9S Range 24E	NMPM Chaves County	
	ation (Show whether DR, RKB, RT, 3558' GR		
	e Box to Indicate Nature of N		
NOTICE OF INTENTIO	N TO:	SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AN	D ABANDON REMEDIAL	CASING	
TEMPORARILY ABANDON CHANGE		DE DRILLING OPNS	
PULL OR ALTER CASING MULTIPLI COMPLE			
OTHER:		Set surface casing	X
Describe proposed or completed operations. (starting any proposed work). SEE RULE 1103 recompilation.	Clearly state all pertinent details, and For Multiple Completions: Attac	d give pertinent dates, including estimated date of h wellbore diagram of proposed completion or	of
	ools with 12-1/4" hole at 1:00 F	PM on 4/17/02. Notified Van Barton with	
NMOCD by voice mail.		, ,	
4/18/02 - Reached TD of 12-1/4" hole of			
		stuck 50' off bottom. Received verbal	
permission from Bryan Arrant to cemer	at casing there.) Texas Pattern	guide shoe set at 872'. Insert float set a	† C 1
829,24', Cemented with 100 sxs A + RF	C (yla 1.62, Wt 14.2) and 400 s	xs 35/65 Poz C + 6% D20 + 5 pps D24 + 2% d 1.32, wt 14.8). PD at 12:45 PM. Bumpe	۲4 20
plug to 768#, held OK. Did not circulat		a 1.02, wi 14.0j. 1 D ai 12.40 i W. Dompe	·u
		Van Barton with OCD to redimix to surfac	ce.
Redimix with 4 yards.			
4/19/02 – Drilled out at 10:15 AM. WO	C 21-1/2 hours. Reduced hole	to 7-7/8" and resumed drilling.	
I hereby certify that the information above is t	rue and complete to the best of my k	mowledge and belief.	
SIGNATURE Line Harpen	TITLE Engineerin	g Technician DATE April 22, 2002	
Type or print name Syson Herpin		Telephone No. 505-748-147	71
CTC C. C. C. C.			
///// UNIGHAL 3	IGNED BY TIM W. GUM SUPERVISOR ITLE	DATE AR 2	5 21
Conditions of approval, if any:			