	- CIXI
Submit 3 Copies To Appropriate District State of New Mexico	Form C-103
Office Energy, Minerals and Natural Res	ources Revised March 25, 1999 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 District II	00 005 10441
811 South First, Artesia, NM 88210 OIL CONSERVATION DIVIS	5 Indicate Type of Lease
District III 1000 Rio Brazos Rd., Aztec, NM 87410 1220 South St. Francis Dr	STATE X FEE
District IV	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	LG-2622
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name: K TO A Harvest ABR State
1. Type of Well: Oil Well Gas Well X Other	222
2. Name of Operator	7. Well No.
Yates Petroleum Corporation	7. Well No. #3 8. Pool name or Wildcat
3. Address of Operator	8. Pool name or Wildcat
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well X Other 2. Name of Operator Yates Petroleum Corporation 3. Address of Operator 105 S. 4th Street Artesia, NM 88210	Wildcat Basement
4. Well Location	
Unit Letter J: 1980 feet from the South line are 1980 feet from the East line	
Section 36 Township 9S Range 24E	NMPM Chaves County
10. Elevation (Show whether DR, RKB,	RT, GR, etc.)
3558' GR	CN 4: Description Date
11. Check Appropriate Box to Indicate Nature of	SUBSEQUENT REPORT OF:
NOTICE OF INTENTION TO:	— ALTERING
PERFORM REMEDIAL WORK PLUG AND ABANDON REME	CASING CASING
	MENCE DRILLING OPNS PLUG AND ABANDONMENT
	NG TEST AND NT JOB
OTHER:	R: Set intermediate casing X
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.	
4/19/02 – Lost full returns at 1074'. Pumped LCM sweeps. Could not get returns back.	
Drilled to 1600'. TD 7-7/8" hole at 10:15 PM. Ran 37 joints (1606.25') of 7" 23# J-55 casing set at 1600'. Texas Pattern guide shoe set at 1600'. Float collar	
set at 1556.20'. Cemented with 200 sxs C + 2% CaCl2 (yld 1.32, wt 14.8)	
4/20/02 PD at 7:30 AM. Bumped plug to 1190#, float did not he	old. Shut cement head in. WOC.
4/21/02 – Drilled out at 9:45 AM. WOC 26 hours 15 minutes. Red	uced hole to 6-1/8" and resumed drilling.
I hereby certify that the information above is true and complete to the best of	my knowledge and belief.
SIGNATURE Main TITLE Engine	ering Technician DATE April 22, 2002
Type or print name Sysan Herpin	Telephone No. 505-748-1471
(This space for States)	
A PPPROVED BY ORIGINAL SIGNED BY TIM W. GUIS DATER 2 8 202	
Conditions of approval, if any:	