

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

WELL API NO.

**30-005-63461**

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

**VA-2090**

7. Lease Name or Unit Agreement Name:

**Expenditure AXV State**

7. Well No.

**#1**

8. Pool name or Wildcat

**Foor Ranch PrePermian**

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

**Yates Petroleum Corporation**

3. Address of Operator

**105 S. 4<sup>th</sup> Street Artesia, NM 88210**

4. Well Location

Unit Letter **D** : **660** feet from the **North** line and **990** feet from the **West** line

Section **9** Township **10S** Range **26E** NMPM **Chaves** County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

**3797' GR**

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Perforate and Acidize ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/23/02 - Perf basement 6138'-6150' (2 SPF, 26 holes), 6066'-6074' (2 SPF, 18 holes).

5/24/02-5/27/02 - Spot 1 bbl of 7-1/2% acid at 6155'.

5/28/02 - Set CIBP at 6050' with 30' cement on top. Perforate Silurian Dolomite 5860'-5864' (4 SPF, 20 holes), 5878-5888' (4 SPF, 44 holes), 5902'-5912' (4 SPF, 84 holes; for a total of 148 holes).

5/30/02 - Acidize well with 3400 gals of 20% IC acid and 198 balls.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE June 5, 2002

Type or print name Tina Huerta

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

APPROVED BY [Signature]

DATE JUN 12 2002

Conditions of approval, if any:

THE UNIVERSITY OF CHICAGO  
LIBRARY