

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

c15' BP

Form C-103

Revised March 25, 1999

WELL API NO.

30-005-63486

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

VA-1617

7. Lease Name or Unit Agreement Name:

Oliver BAI State

8. Well No.

1

9. Pool name or Wildcat

Palma Mesa Penn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG-BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter E : 1800 feet from the North line and 660 feet from the West line

Section 29 Township 8S Range 27E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3712' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE
COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING
CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND
ABANDONMENT ☒

CASING TEST AND
CEMENT JOB ☐

OTHER: ☐

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/26/02 - Plugging well. Spotted 100 bbl hi-vis on bottom. TIH with drill collars and laid down. TIH with drill pipe open ended. Circulate. Laid down 17 joints drill pipe. Break circulation to spot first cement plug at 6317' (100' plug) Strawn. NOTE: Plugging instruction given by Jerry Guy at NMOCD at 6:30 PM.

7/27/02 - Released rig. Spotted cement plug at 6317' Strawn (100') w/35 sx Class "C" Neat. Laid down 30 joints drill pipe. Spot cement plug at 5380' Wolfcamp (100') w/35 sx Class "C" Neat. Laid down 17 joints drill pipe. Spot cement plug at 4833' Abo (100') w/35 sx Class "C" Neat. Laid down 74 joints drill pipe. Spotted cement plug at 2517' Glorieta (100') w/35 sx Class "C" Neat. Laid down 47 joints drill pipe. Spotted cement plug at 1050' (100') w/50 sx Class "C" with additives (shoe 8-5/8"). TOH 17 stands and WOC. TIH with 16 stands and tagged at 1020'. Spotted cement plug at 1020' (100') w/50 sx Class "C" with additives (shoe). TOH with 16 stands and WOC. TIH and tagged at 880'. Laid down 23 joints drill pipe. Spot cement plug at 305' Yates (100') w/35 sx Class "C" with additives. Laid down 8 joints drill pipe. Spot cement plug at 60' to surface w/30 sx Class "C" with additives. Laid down 2 joints. Nippled down Larkin head. Jet pits. Rigging down. Rig released at 1:00 AM 7/28/02. PLUGGED AND ABANDONED. FINAL REPORT.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE July 30, 2002

Type or print name Tina Huerta

Telephone No. 505-748-1471

(This space for State use)

APPROVED BY Recd Only TITLE _____

DATE _____

Conditions of approval, if any:

AUG 7 2002