

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

CIST  
OP

Form C-103  
Revised March 25, 1999

WELL API NO.  
30-005-63512

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Exacta AXE State

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter B : 660 feet from the North line and 1980 feet from the East line

Section 9 Township 10S Range 26E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3810' GR

7. Well No.

1

8. Pool name or Wildcat

Wildcat Precambrian

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

CASING TEST AND CEMENT JOB ☐

OTHER:

☐

OTHER: Set surface casing

☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

12/24/02 - Ran 28 joints 8-5/8" 24# J-55 ST&C casing set at 1154'. Texas Pattern Guide shoe set at 1154'. Insert float set at 1112'. Cemented with 500 sx 35:65 Poz "C" with additives (yld 1.99, wt 12.6). Tailed in with 200 sx "C" with additives (yld 1.32, wt 14.8). Cement circulated. WOC 44 hrs 45 mins. Reduced hole to 7-7/8" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jina Huerta TITLE Regulatory Compliance Supervisor DATE January 6, 2003

Type or print name Jina L. Huerta

Telephone No. 505-748-1471

(This space for State use)  
**ORIGINAL SIGNED BY TIM W. GUM**  
**DISTRICT II SUPERVISOR**

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_

DATE \_\_\_\_\_

Conditions of approval, if any:

**JAN 14 2003**