
Wichita Industries, Ir - #1-13 Federal NTL-6 Multipoint Requi_ments Surface Use and Operations Plan Page Three



4. Location of Existing and/or Proposed Facilities: 1. S. GEOLO

S. GEOLOGICAL SURVEY

A. Existing Facilities:

- (1) No existing production facilities are located within a two-mile radius of the proposed well.
- (2) No oil gathering lines are located within a two-mile radius of the proposed well.
- (3) No gas gathering lines are located within a two-mile radius of the proposed well.
- (4) No injection lines are located within a two-mile radius of the proposed well.
- (5) No disposal lines are located within a two-mile radius of the proposed well.

B. New Facilities Contemplated:

- (1) A pumping unit heater-treater, flow lines, and tank battery will be installed if the well is successfully completed as a producer. All this equipment will be located on the drilling location as shown in Exhibit "C".
- (2) All flow lines will be buried at least 18 inches deep. No oil sales lines are anticipated unless several wells are completed successfully.
- (3) The production facilities are located on Exhibit "C". The size of the pumping unit will be 16,000 in. 1b. to 57,000 in. 1b. gear box depending on the capacity of the well. The size of the storage tanks and heater-treater will also depend on the production capacity of the well. No more than two 210 barrel welded tanks (10' dia. by 20' high) are anticipated. The storage tanks treater, and water disposal facilities will be located next to the present road.
- (4) The locations of the production facilities are shown on Exhibit "C".
- (5) The oil flow lines will be constructed out of steel or fiberglass. If a pumping unit is installed, it will either be a wide steel base unit installed on 3' x 12' planks on a gravel pad or a narrow base unit installed on a concrete pad.
- (6) The produced water, if any, will be stored in a 100-barrel fiberglass tank. If the water production is too much, a plastic lined pit will be used. The pumping unit will have guard installed over the V-belts and a railing around the crank arms and counterbalance weights.