

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

JAN 11 1980

O. C. O.
ARTESIA OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

6a. Indicate Type of Lease State ☒ Fee ☐
8. State Oil & Gas Lease No. LG-0401
7. Unit Agreement Name
8. Farm or Lease Name State GK
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat Wolfcamp
12. County De Baca

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR NOTICES AND REPORTS ON WELLS THAT ARE NOT PRODUCING OR ARE ABOUT TO BE PRODUCED IN A DIFFERENT RESERVOIR. USE STATE FORM C-104 FOR SUCH PURPOSES.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
Amoco Production Company ✓

Address of Operator
P. O. Box 68, Hobbs, NM 88240

Location of Well
UNIT LETTER F 1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE West LINE, SECTION 32 TOWNSHIP 1-N RANGE 26-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3955.7 GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE GRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE HOLE 1103.

Propose to plug and abandon well by the following procedure:

- Spot a25 sx Class H cement plug from 4600'-4700' above perforated interval 4730'-4866'.
- Spot a25 sx Class H cement plug from 3560'-3660' across top of Abo.
- Spot a25 sx Class H cement plug from 3120'-3220' across top of Tubb.
- * Spot a25 sx Class H cement plug from 1700'-1800' across top of Yeso.
- Spot a25 sx Class H cement plug from 310'-410' across top of Rustler Anhydrite.
- Spot a 20 sx Class H cement surface plug. Erect permanent P x A marker. Clean and level location.
- * Spot a 25 sx Class H cement plug at 800' across 9 5/8" casing shoe set at 720'.

I, hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Assistant Admin. Analyst DATE 1-11-80

APPROVED BY W.A. G. G. G. TITLE SUPERVISOR, DISTRICT II DATE JAN 15 1980

CONDITIONS OF APPROVAL, IF ANY:
0+4 NMOC-A 1-Hou 1-Susp 1-RD