

OIL CONSERVATION DIVISION
P. O. BOX 2038
SANTA FE, NEW MEXICO 87501Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

DEC 3 1981

O. C. D.

1. Indicate Type of Lease State ☒ Fee ☐
2. State Oil & Gas Lease No. LG-747
3. Unit Agreement Name
4. Farm or Lease Name State 17
5. Well No. 1
6. Field and Pool, or Wildcat Wildcat
7. County DeBaca

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL DEEPER TO DEPTH OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT - "A" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐
2. Name of Operator Flag-Redfern Oil Company
3. Address of Operator P.O. Box 2280 Midland, Texas 79702
4. Location of Well UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 17 TOWNSHIP 1-S RANGE 25-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
4011.7 GR

10. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPNS. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOBS ☐
OTHER ☐	OTHER Completion attempt in Abo formation ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Evaluated Abo Formation

11-17-81 Perforated with 2 JSPF from 3951-54, 3939-46, 3870-74, 3836-39 (34 holes).
Acidized with 3000 gals. 15% Morrow Flow, 1000 SCF nitrogen per bbl.
Max. press. 3900 psig, Avg. Press. 3150 psig at 3.1 BPM. ISIP-1900 psi.
Flowed and swabbed. Swabbed dry. No burnable gas.
Set CIBP at 3830'. Tested plug to 4000 psig.

11-23-81 Perforated with 2 JSPF from 3798-3801, 3788-93, 3744-47, 3714-19, 3702-06, (34holes)
Acidized with 3000 gals. 15% Morrow Flow acid, 1000 SCF nitrogen per bbls.
Max. Press. 3300 psig, Avg. Press. 2800 psig at 3.8 BPM ISIP-1700 psig. Flowed
and swabbed to recover acid water. Swabbed dry. No burnable gas.
Set CIBP at 3696'. Tested plug to 4000 psig.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Byron W. Freeman TITLE Engineer DATE 12-2-81APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE DEC 9 1981

CONDITIONS OF APPROVAL, IF ANY: