

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐  
well well other

2. NAME OF OPERATOR  
Hunt Oil Company ✓

3. ADDRESS OF OPERATOR  
2900 First Nat'l Bank Bldg, Dallas, TX 75202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) Set intermediate string casing (8-5/8")

5. LEASE

NM 26518

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cooper Ranch Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 30, T4N, R22W

12. COUNTY OR PARISH

DeBaca

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

4914' GL, 4925' DF, 4926' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-26-82: Ran 8-5/8" casing set at 2509' and cemented with 1,000 sx Halliburton Light, 1/4# Flocele/sx and 350 sx Class C, 2% CaCl, 1/4# Flocele/sx. Circulated 40 sx to pit. (24#, K-55 casing)

Subsurface Safety Valve: Manu. and Type N/A Set @                      Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Eugene A. Thompson TITLE District Engineer DATE 8-11-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

(ORIG. SGD) DAVID R. GLASS

APPROVED BY  
CONDITIONS OF

APPROVAL IF ANY:

OCT 14 1982

TITLE

DATE

U.S. GEOLOGICAL SURVEY  
ROSWEEL, NEW MEXICO

See Instructions on Reverse Side