

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐ **OCT 15 1982**
2. NAME OF OPERATOR **O. C. D.**
Hunt Oil Company ☒ **ARTESIA, OFFICE**
3. ADDRESS OF OPERATOR
2900 First Nat'l Bank Bldg, Dallas, TX 75202
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Set production casing (5-1/2")		

5. LEASE
NM 26518
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-
7. UNIT AGREEMENT NAME
-
8. FARM OR LEASE NAME
Cooper Ranch Federal
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 30, T4N, R22W
12. COUNTY OR PARISH
DeBaca
13. STATE
New Mexico
14. API NO.
-
15. ELEVATIONS (SHOW DF, KDB, AND WD)
4914' GL, 4925' DF, 4926' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-11-82: Ran 5-1/2" casing set at 4504' and cemented with 900 sx 50-50 Class C-Pozmix A, 2% Gel, 6# Salt, 0.4% Halad-4, 0.3% CFR-2, 1/4# Flocele/sx. Top Cement 2664'. (15.5#, K-55 casing)

Subsurface Safety Valve: Manu. and Type **N/A** Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *David R. Glass* TITLE **District Engineer** DATE **8-11-82**

ACCEPTED FOR RECORD

(ORIG. SGD.) **DAVID R. GLASS** (Use space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL IF ANY: **10/1/1982**

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side