REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE

PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** ABANDON\*

REPAIR WELL

(other)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUBSEQUENT REPORT OF:

| UNITED STATES  DEPARTMENT OF THE INTERIOR   | 5. LEASE<br>NM 26518  |  |  |
|---|---|--|--|
| GEOLOGICAL SURVEY   | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME -                            |  |  |
| SUNDRY NOTICES AND REPORTS ON WELLS   | 7. UNIT AGREEMENT NAME<br>-                                       |  |  |
| (Do not use this form for proposals to drill or to deaper CENVEDck to a different reservoir. Use Form 9–331–C for such proposals.)                | 8. FARM OR LEASE NAME<br>Cooper Ranch Federal                     |  |  |
| 1. oil see see see see see see see see see se   | 9. WELL NO.   |  |  |
| 2. NAME OF OPERATOR  Hunt Oil Company  O. C. D.   | 10. FIELD OR WILDCAT NAME Wildcat                                 |  |  |
| 3. ADDRESS OF OPERATOR ARTESIA, OFFICE 2900 First Nat'l Bank Bldg, Dallas, Texas 75203 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 |   |  |  |
| below.) AT SURFACE: AT TOP PROD. INTERVAL:  | 12. COUNTY OR PARISH 13. STATE DeBaca New Mexico                  |  |  |
| AT TOTAL DEPTH: 4505'  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,  | 14. API NO.   |  |  |
| REPORT, OR OTHER DATA   | 15. ELEVATIONS (SHOW DF, KDB, AND WD 4914' GL, 4925' DF, 4926' KB |  |  |

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Verbal approval received for the plugging of the well.

Set CIBP at 4030' capped with 35' cement Set CIBP at 2925' capped with 35' cement Set CIBP at 1350' capped with 35' cement Set 5 sx cement at Surface Weld cover plate on 13-3/8" casing Weld Dry Hole Marker on Cover Plate

10月14年82

M



OIL & GAS U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO

| Subsurface Safety Valve: Manu. and Type         | N/A   | Set @   | Ft. |
|---|---|---------|-----|
| 18. I hereby certify that the foregoing is true | and correct  TITLE District Engineer DATE             | 8-10-82 | · . |
| APPROVED BY (ORIG. SGD.) DAVID R'               | nis space for Federal or State office use)  OLASS DAT | TE      | _•  |