

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Drawer DD
Artesia, NM 88210

LEASE

NM 17201

RECEIVED

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

JAN 18 1983

8. FARM OR LEASE NAME

Big Bend WJ Federal

O. C. D.

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit M, Sec. 35-T3S-R25E

12. COUNTY OR PARISH

De Baca

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3798.9' GR

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990 FSL & 990 FWL, Sec. 35-3S-25E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

☒

☐

☐

☐

☐

☐

☐

☐

☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 12-1/4" hole at 5:00 PM 12-31-82. Ran 21 joints of 8-5/8" 24# J-55 ST&C casing set at 914'. 1-Type "M" guide shoe at 914'. Insert float at 871'. Cemented w/400 sacks Pacemaker Lite 3% CaCl₂. Tailed in w/300 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 2:10 AM 1-6-82. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out at 8:10 PM 1-6-83. WOC 18 hours. Nipped up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass TITLE Production Supervisor DATE 1-10-83

APPROVED BY
CONDITIONS

ACCEPTED FOR RECORD (This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

JAN 17 1983

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

JAN 11 1983

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO