

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NO SUBMIT IN FR
MODEL (CARS)
DRAWER DD
Artesia, NM 88210

Budget Bureau No. 1004-0135
Expires August 31, 1985
LEASE DESIGNATION AND SERIAL NO.

NM 19988

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | |
|--|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| 2. NAME OF OPERATOR Yates Petroleum Corporation | 7. UNIT AGREEMENT NAME |
| 3. ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210 | 8. FARM OR LEASE NAME Kidd ZF Federal |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980 FNL & 660 FWL, Sec. 26-1N-26E | 9. WELL NO. 1 |
| 14. PERMIT NO. | 10. FIELD AND POOL, OR WILDCAT Wildcat |
| 15. ELEVATIONS (Show whether OF, RT, GR, etc.) 3960.4' GR | 11. SEC., T., S., M., OR BLK. AND SURVEY OR AREA Unit E, Sec. 26-T1N-R26E |
| | 12. COUNTY OR PARISH DeBaca |
| | 13. STATE NM |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENT ON TO:

| | |
|--|---|
| TEST WATER SHUT-OFF <input type="checkbox"/> | PULL OR ALTER CASING <input type="checkbox"/> |
| FRACTURE TREAT <input type="checkbox"/> | MULTIPLE COMPLETE <input type="checkbox"/> |
| SHOOT OR ACIDIZE <input type="checkbox"/> | ABANDON* <input type="checkbox"/> |
| REPAIR WELL <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> |
| (Other) <input type="checkbox"/> | |

SUBSEQUENT REPORT OF:

| | |
|---|--|
| WATER SHUT-OFF <input type="checkbox"/> | REPAIRING WELL <input type="checkbox"/> |
| FRACTURE TREATMENT <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| SHOOTING OR ACIDIZING <input checked="" type="checkbox"/> | ABANDONMENT* <input type="checkbox"/> |
| (Other) <input type="checkbox"/> | |

Production Csg. Perforate, Tre ☒
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 5962'. Ran 45 joints of 5-1/2" 14# J-55 casing set at 1890'. 1-regular guide shoe set at 1889'. Float collar set at 1847'. Cemented w/850 sacks High Early with 5% D-44X and 1/2% D-60. Yield 1.35, Slurry 14.7. PD 9:45 PM 4-14-84. Bumped plug to 1000 psi, held for 30 minutes, released pressure and float held okay. WOC 18 hours. WIH and perforated 1355-59' w/10 .50" holes (2 SPF). Acidized perforations 1355-59' w/1000 gallons 15% NEFE acid and ball sealers. No show of oil or gas. WIH and perforated 1482-1530' w/12 .50" holes as follows: 1482, 33, 84, 86, 97, 1503, 09, 18, 25, 28, 29 and 30'. Acidized perforations 1482-1530' w/2000 gallons 15% NEFE acid and ball sealers. Swabbed well. No show of oil or gas. Set CIBP at 1310' w/15' cement on top. WIH and perforated 1040-1183' w/15 .50" holes as follows: 1040, 41, 52, 64, 68, 89, 1100, 18, 19, 45, 56, 62, 63, 78 and 83'. Tested CIBP to 3000#, OK. Acidized perforations 1040-1183' w/3000 gallons 15% NEFE acid and ball sealers. No show of oil or gas.

18. I hereby certify that the foregoing is true and correct

SIGNED Peter W. Webster TITLE Production Supervisor DATE 5-1-84

(This space for Federal or State office use)

APPROVED BY PETER W. WEBSTER TITLE Production Supervisor DATE MAY 16 1984

CONDITIONS OF APPROVAL, IF ANY

*See Instructions on Reverse Side