

**NEW MEXICO OIL CONSERVATION COMMISSION**  
Santa Fe, New Mexico

**MISCELLANEOUS REPORTS ON WELLS**

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

**Indicate Nature of Report by Checking Below**

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	<b>X</b>	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

**January 23, 1953**

(Date)

**Hobbs, New Mexico**

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

**Cities Production Corporation**

(Company or Operator)

**Hobson**

(Lease)

**Makin Drilling Company**

(Contractor)

Well No. **1** in the **NE**  $\frac{1}{4}$  of Sec. **12**

T. **1S**, R. **27E**, NMPM., **Wildcat** Pool, **DeBaca** County.

The Dates of this work were as follows: **January 4 & 5, 1953**

Notice of intention to do the work (was) (~~was~~/not) submitted on Form C-102 on **January 2**, 19**53**,  
(Cross out incorrect words)

and approval of the proposed plan (was) (~~was~~/not) obtained.

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

Hobson No. 1 was drilled to a total depth of 6742' in Granite. 13 3/8" OD H-40 SS Csg. was set at 384' and left in the hole, cement circulated. 8 5/8" OD 24# J-55 SS Csg. was set at 2288.5' and left in the hole, cement circulated. The hole was loaded with approximately 430 barrels of 9.7# mud laden fluid. Three cement plugs were spotted: 50 sacks cement at 6500' to 6338'; 25 sacks 4000' to 3919'; 25 sacks 2296' to 2215'. An additional 30' plug was placed in the top of 8 5/8" Csg. A 3" pipe marker has been installed to mark the abandoned location. Plugging was witnessed by O. D. Duncan, Box 97, Hobbs, New Mexico and A. P. Coe, Box 126, Lunice, New Mexico, engineer and assistant production foreman respectively, and Otho Ward, tool pusher for Makin Drilling Company, residing at 612 East Gypsy Street, Hobbs, New Mexico. Preliminary clean-up has been made but some additional work will have to be performed when sufficiently dry to leave location in the desired condition.

Witnessed by **C. M. Hartwell** **Cities Service Oil Company** **District Superintendent**  
(Name) (Company) (Title)

Approved: **OIL CONSERVATION COMMISSION**

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name **Charles M. Hartwell**

Position **District Superintendent**

Representing **Cities Service Oil Company**

Address **Box 97, Hobbs, New Mexico**

(Title)

(Date)