

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

November 6, 1952

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Cities Production Corporation

(Company or Operator)

Hobson

(Lease)

Makin Drilling Company

(Contractor)

Well No. 1 in the NE 1/4 NE 1/4 of Sec. 12

T-1-S, R. 27-E, NMPM, Undesignated Pool, DeBaca County.

The Dates of this work were as follows: November 2 to November 6, 1952

Notice of intention to do the work (was) ~~not~~ submitted on Form C-102 on November 5, 1952, (Cross out incorrect words)and approval of the proposed plan ~~was~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well was drilled to a total depth of 387' in Red Bed. Ran 11 joints (368') of 13 3/8" OD 48# casing set at 384' and cemented with 425 sacks. Plug was down at 9:40 A.M., November 2, 1952. Pumped plug to 343 and cement had circulated. Let set 12 1/2 hours and cement had fallen. Recemented with 133 sacks, 4% gel and 11 sacks strata crete. Plug was down at 9:30 A.M., November 3, 1952. Ran temperature survey and found cement at 362' and some cement channeled behind the pipe as high as 335'. Perforated with 2-1/2" holes and recemented with 200 sacks. Ran temperature survey and found top of cement at 151. Reperforated with 2-1/2" holes and cemented with 168 sacks of cement. Cement circulated. Cement was allowed to set 24 hours. 1000# pressure applied with all valves closed with no drop in pressure. Test was satisfactory and drilling was resumed.

Witnessed by R. E. Fly Cities Production Corporation District Superintendent
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

Position District Superintendent

Representing Cities Production Corporation

Address Box 97, Hobbs, New Mexico

(Name)

(Title)

(Date)