



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Danciger Oil & Refining Co., 14th Floor, W. T. Waggoner Bldg., Ft. Worth, Texas
Company or Operator Address
State Well No. 1-A in SE 1/4 NE 1/4 of Sec. 8, T. 2 S
R. 26 E, N. M. P. M., Wildcat Field, DeBaca County.
Well is 1980 feet south of the North line and 660 feet west of the East line of Sec. 8
If State land the oil and gas lease is No. 2 8885 Assignment No. _____
If patented land the owner is _____ Address _____
If Government land the permittee is _____ Address _____
The Lessee is _____ Address _____
Drilling commenced October 12, 19 43 Drilling was completed December 15th 19 43
Name of drilling contractor Kersey & Co. Address Artesia, N. Mex.
Elevation above sea level at top of casing 4080 feet.
The information given is to be kept confidential until _____ 19 _____

OIL SANDS OR ZONES

No. 1, from _____ to _____ No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from 1835' to 275' feet. Water level 150' from surface
No. 2, from 1810' to 1880' feet. Salt Water - water level 150' from surface
No. 3, from _____ to _____ feet. _____
No. 4, from _____ to _____ feet. _____

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
<u>12 1/2"</u>	<u>45#</u>	<u>8</u>	<u>?</u>	<u>305'</u>	<u>Collar</u>				
<u>10"</u>	<u>32#</u>	<u>8</u>	<u>?</u>	<u>684'</u>	<u>Texas</u>				
<u>8 1/4"</u>	<u>28#</u>	<u>8</u>	<u>?</u>	<u>1078'</u>	<u>Texas</u>				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
Cable tools were used from 0 feet to 1890 feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing _____ 19 _____
The production of the first 24 hours was _____ barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

D. E. Brookover Driller Dan Webb Driller
_____ Driller _____ Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	50'	50	Red Clay
50	95'	45	Red Sand
95	190'	95	Red Beds
190	210'	20	Yellow Rock
210	220'	10	Gray Rock
220	230'	10	Lime
230	265'	35	Red Beds
265	275'	10	WATER SAND
275	305	30	Red Beds
305	335	30	Sand
335	370	35	Red Beds
370	410	40	Sand & Shale
410	420	10	Red Beds
420	425	5	Red Sand
425	455	30	Sand & Red Rock
455	475	20	Anhydrite
475	490	15	Blue Shale
490	495	5	Anhydrite
495	520	25	Blue Shale
520	525	5	Anhydrite
525	570	45	Anhydrite & Red Beds
570	575	5	Red Beds
575	620	45	Anhydrite & Red Beds
620	635	15	Red Beds
635	650	15	Anhydrite & Red Beds
650	655	5	Brown Sand
655	910	255	Red Beds
910	925	15	Anhydrite & Red Beds
925	1130	205	Red Beds
1130	1142	12	Gray Lime
1142	1145	3	Blue Shale
1145	1160	15	Gray Lime
1160	1165	5	Blue Shale
1165	1183	18	Gray Lime
1183	1185	2	Blue Shale
1185	1220	35	Gray Lime
1220	1245	25	Hard Black Lime
1245	1365	120	Gray Lime
1365	1385	20	Black Lime
1385	1425	40	Gray Lime
1425	1440	15	Blue Shale
1440	1465	25	Brown Sand
1465	1495	30	Salt
1495	1540	45	Gray Lime - Top San Andres Lime
1540	1600	60	Black Lime
1600	1635	35	Gray Lime
1635	1735	100	Black Lime
1735	1780	45	Gray Lime
1780	1810	30	Black Lime
1810	1880	70	Glorietta Sand - Salt Water
1880	1890	10	Blue Shale - Total Depth