

N

## NEW MEXICO OIL CONSERVATION COMMISSION


Santa Fe, New Mexico

|  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |

AREA 640 ACRES  
LOCATE WELL CORRECTLY

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPlicate. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.



**Firesafe Builders Products Corp,** **Providence, R.I.**  
 Company or Operator Address  
 State                      Well No. 1 in NENE of Sec. 8, T. 3S  
 Lease  
 R. 26E N. M. P. M.                      Field, DeBaca County.  
 Well is 330' feet south of the North line and 330' feet west of the East line of                       
 If State land the oil and gas lease is No.                      Assignment No.                       
 If patented land the owner is                      Address                       
 If Government land the permittee is                      Address                       
 The Lessee is                      Address                       
 Drilling commenced Approx Aug 17 19 45 Drilling was completed Dec 20 19 1945  
 Name of drilling contractor A D Engle & Co Address Okla City, Okla  
 Elevation above sea level at top of casing                      feet.  
 The information given is to be kept confidential until                      19                     

## OIL SANDS OR ZONES

No. 1, from                      to                      No. 4, from                      to                       
 No. 2, from                      to                      No. 5, from                      to                       
 No. 3, from                      to                      No. 6, from                      to                     

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from                      to                      feet.                       
 No. 2, from                      to                      feet.                       
 No. 3, from                      to                      feet.                       
 No. 4, from                      to                      feet.                     

## CASING RECORD

| SIZE        | WEIGHT PER FOOT | THREADS PER INCH | MAKE | AMOUNT      | KIND OF SHOE | CUT & FILLED FROM | PERFORATED |    | PURPOSE |
|-------------|-----------------|------------------|------|-------------|--------------|-------------------|------------|----|---------|
|             |                 |                  |      |             |              |                   | FROM       | TO |         |
| <u>85/8</u> | <u>28</u>       | <u>8</u>         |      | <u>415</u>  |              |                   |            |    |         |
| <u>51/2</u> | <u>13</u>       | <u>8</u>         |      | <u>1487</u> |              |                   |            |    |         |
|             |                 |                  |      |             |              |                   |            |    |         |
|             |                 |                  |      |             |              |                   |            |    |         |
|             |                 |                  |      |             |              |                   |            |    |         |
|             |                 |                  |      |             |              |                   |            |    |         |
|             |                 |                  |      |             |              |                   |            |    |         |

## MUDDING AND CEMENTING RECORD

| SIZE OF HOLE | SIZE OF CASING | WHERE SET | NO. SACKS OF CEMENT | METHOD USED | MUD GRAVITY | AMOUNT OF MUD USED |
|--------------|----------------|-----------|---------------------|-------------|-------------|--------------------|
|              |                |           |                     |             |             |                    |
|              |                |           |                     |             |             |                    |
|              |                |           |                     |             |             |                    |
|              |                |           |                     |             |             |                    |

## PLUGS AND ADAPTERS

Heaving plug—Material                      Length                      Depth Set                       
 Adapters—Material                      Size                     

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

| SIZE | SHELL USED | EXPLOSIVE OR CHEMICAL USED | QUANTITY | DATE | DEPTH SHOT OR TREATED | DEPTH CLEANED OUT |
|------|------------|----------------------------|----------|------|-----------------------|-------------------|
|      |            |                            |          |      |                       |                   |
|      |            |                            |          |      |                       |                   |
|      |            |                            |          |      |                       |                   |

Results of shooting or chemical treatment                     

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from 0 feet to 1831 feet, and from                      feet to                      feet  
 Cable tools were used from                      feet to                      feet, and from                      feet to                      feet

## PRODUCTION

Put to producing                      19                       
 The production of the first 24 hours was                      barrels of fluid of which                      % was oil;                      % emulsion;                      % water; and                      % sediment. Gravity, Be                       
 If gas well, cu. ft. per 24 hours                      Gallons gasoline per 1,000 cu. ft. of gas                       
 Rock pressure, lbs. per sq. in.                     

## EMPLOYEES

Lee Broughton Driller Joe Dyer Driller  
Warren Broughton Driller                      Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 27

December 19 45  
Frederick Howard  
 Notary Public

My Commission expires May 4, 1947

Albuquerque Dec 27 1945

Place                      Date                     Name A D EnglePosition LeaseRepresenting Firesafe Builders Products Co

Company or Operator

Address Providence, R.I.

## FORMATION RECORD

| FROM | TO   | THICKNESS<br>IN FEET | FORMATION                              |
|------|------|----------------------|--|
| 0    | 210  |                      | Sand                                   |
| 210  | 290  |                      | Sand (Soft) (White)                    |
| 290  | 300  |                      | Broken sand and shell (White)          |
| 360  | 422  |                      | Red bed (Red)                          |
| 422  | 750  |                      | Red bed and shale (Red and White)      |
| 750  | 970  |                      | Sand and Sandy lime (White)            |
| 970  | 1000 |                      | Lime and gyp shell (White and hard)    |
| 1000 | 1015 |                      | Salt and potash (Red and White) (Soft) |
| 1015 | 1025 |                      | Lime (White and hard)                  |
| 1025 | 1035 |                      | Lime (Gray and hard)                   |
| 1035 | 1247 |                      | Lime (Gray and Hard)                   |
| 1247 | 1271 |                      | Lime (Gray and hard)                   |
| 1271 | 1311 |                      | Lime (Sandy, dark and hard) Gas showed |
| 1311 | 1337 |                      | Lime (Sandy, dark and hard)            |
| 1337 | 1412 |                      | Lime (Gray and hard)                   |
| 1412 | 1540 |                      | Salt and potash (White and red) (Soft) |
| 1540 | 1593 |                      | Lime (Brown and hard)                  |
| 1593 | 1620 |                      | Lime (Gray and hard)                   |
| 1620 | 1828 |                      | Lime (Brown and hard)                  |
| 1828 | 1831 |                      | Glorieta Sand (Soft)                   |