Form 9-331 a (Feb. 1951)

APPROVED

JAN 3 1943

WILLIAM H. FELDMILLER

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	Budget Bureau No. 42-R358.4. Approval expires 12-31-60.
Land O	ffice
Lease N	0,
Unit	9
	asky to ST

NOTICE OF INTENTION TO DRILL			
NOTICE OF INTENTION TO TEST WATER SHIP		SUBSEQUENT REPORT OF WATER SHUT-OFF	
I TEST WATER SHUT-O	FF	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	1
NOTICE OF INTENTION TO RE-DRILL OR REPAIR	WELL	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	_	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.	
NOTICE OF INTENTION TO PULL OR ALIER CASH	NG	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO ABANDON WELL	·	SUPPLEMENTARY WELL HISTORY	
(INDICATE ABOVE B	Y CHECK MARK N	ATURE OF REPORT, NOTICE, OR OTHER DATA)	
		January 2	1963
Vell No. 1 is located 660	·		194
ell No. 1 is located 660	It. Irom_	$\{S\}$ line and660 ft. from $\{E\}$ line of sec.	24
it, or may of 2	27	(,,)	
(14 Sec. and Sec. No.) (Tw	***	nge) (Meridian)	
Wildcat (Field)	DoBaca (County or Su	78	
ne elevation of the derrick floor abo	ve sea level	18 4.30% ft.	
	D. 17. 17. 17. 17. 17. 17. 17. 17. 17. 17		
ate names of and avposted door	DETAILS	OF WORK	
	nds; show sizes, w nts, and all other	reights, and lengths of proposed casings; indicate mudding jobs, important proposed work)	cement-
We plen to lay 10	nds; show sizes, we note, and all other	of Work reights, and lengths of proposed casings; indicate mudding jobs, important proposed work) E at 2320. Lay mud blanket to 620. 100' then set cament plug to surface (10 3/4" casing camented at 610')	
We plen to lay 10	nds; show sizes, we note, and all other	reights, and lengths of proposed casings; indicate mudding jobs, important proposed work) 8 42 2320. Lay and blanket to 620.	: e ,
We plen to lay 10	nds; show sizes, we note, and all other	reights, and lengths of proposed casings; indicate mudding jobs, important proposed work) 8 at 2320. Lay mud blanket to 620. 100' then set cament plug to surface (10 3/4" casing camented at 610')	v 5
We plan to lay 10 Lay 10 sack plug at 620 Place marker in 10 3/4"	nds; show sizes, white, and all other secks plus secks plus secks plus secks casing.	reights, and lengths of proposed casings; indicate mudding jobs, important proposed work) 8 at 2320. Lay and blanket to 620. 100' then set cement plug to surface (10 3/4" casing cemented at 610')	V 5 1963
We plan to lay 10 Lay 10 sack plug at 620 Place marker in 10 3/4"	nds; show sizes, white, and all other secks plus secks plus secks plus secks casing.	reights, and lengths of proposed casings; indicate mudding jobs, important proposed work) 8 at 2320. Lay mud blanket to 620. 100' then set cament plug to surface (10 3/4" casing camented at 610')	V 5 1963
We plan to lay 10 Lay 10 sack plug at 620 Place marker in 10 3/4"	nds; show sizes, white, and all other secks plus secks plus secks plus secks casing.	reights, and lengths of proposed casings; indicate mudding jobs, important proposed work) 8 at 2320. Lay and blanket to 620. 100' then set cement plug to surface (10 3/4" casing cemented at 610')	V 5 1963

Description of the second of th