

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other ☐ Plug & Abandon

2. NAME OF OPERATOR

Marshall R. Young Oil Co.

3. ADDRESS OF OPERATOR

P. O. Box 145, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FN EL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☒

5. LEASE

NM 34139

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Saltys Unit

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat - San Juan

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33 T-25-S R-15-W

12. COUNTY OR PARISH

Grant

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

4375 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Total depth 9775' - 9 1/2" open hole. 13 3/8" casing set at 961'-cement circulated, 10 3/4" casing set at 5312', cement circulated. Per BLM recommendations set cement plugs as follows: 70 sxs standard @9775-9625', 85 sxs standard 7650-7500', 95 sx standard 5387-5237' tagged, 80 sxs standard 1050-950', 25 sxs standard 50-0'. Final plug down @9:30 A.M. 12-25-85. Cut off well head 4' below ground level & placed appropriate steel post marker over capped well bore. Mud was left in hole and between cement plugs 8.9#/gal. 64 viscosity 5.4 cc water loss.

No commercial hydrocarbon shows encountered.

Cementing was mixed and pumped by Dowell-Schlumberger thru drill pipe.

Plugging operations commenced 12-24-85 and well plugged and abandoned as of 9:30 A.M. 12-25-85.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Manager

DATE 12-31-85

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED
PETER W. CHESTER

DATE

NOV 3 1986

*See Instructions on Reverse Side

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

Post ID 2

11-14-86

P4A

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.