

#

Operator <u>Arthur B. Ramsey</u>		Lease <u>Ramsey # 25 St</u>		Well # <u>2</u>	
Location of Well	Unit <u>P</u>	Section <u>25</u>	Township <u>27 S.</u>	Range <u>17 W.</u>	County <u>Hidalgo</u>
Drilling Contractor <u>VI-ROI Drlg. Co.</u>	Type of Equipment <u>Rotary</u>				

*** Witness**APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>12 1/4</u>	<u>* 8 5/8</u>	<u>24 #</u>		<u>600</u>	<u>Circ to Surf.</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>15.5 #</u>		<u>3000</u>	<u>500' Above Prod. Form.</u>

Casing Data:

Surface joints of 8 5/8" inch 24 # Grade J-55(Approved) (Rejected)Inspected by M.S. date 7-4-90

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required Type of Shoe used guide Float collar used insert Btm 3 jts welded yesTD of hole 618' Set 618' Feet of 8 5/8" Inch 24 # Grade J-55New-used csg. @ 618' with 400 2%cc sacks neat cement around shoe+ sax additives Plug down @ 9:45 (AM) (PM) Date 7-4-90Cement circulated yes No. of Sacks 55 sxCemented by Halliburton Witnessed by Mike StubblefieldTemp. Survey ran @ (AM) (PM) Date top cement @ Casing test @ (AM) (PM) Date Method Used Witnessed by Checked for shut off @ (AM) (PM) Date Method used Witnessed by Remarks: