

FAFE	1	
	1	
U.S.		
D OFFICE		
RATOR	1	

NEW MEXICO OIL CONSERVATION COMMISSION

C-102 and C-103
Effective 1-1-65

SEP 30 1974

O. C. C.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR TO RE-ENTER A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

IL ☐ GAS ☐ OTHER: Dry Hole

ne of Operator

Mac T. Hall ✓

ress of Operator

Integral Petroleum Corporation, 1816 Guaranty Bk Plaza, Christi, Tex

ation of Well

UNIT LETTER B 990 FEET FROM THE North LINE AND 1980 FEET FROM

East LINE, SECTION 25 TOWNSHIP 32 S RANGE 16 W NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

GR 4575

5a. Indicate Type of Lease

State ☒

Fee ☐

5. State Oil & Gas Lease No.

K-2757

7. Unit Agreement Name

8. Farm or Lease Name

New Mexico, State

9. Well No.

1

10. Field and Pool, or Wildcat

Wildcat

12. County

Hidalgo

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

ORM REMEDIAL WORK ☐

ORARILY ABANDON ☐

OR ALTER CASING ☐

INER ☐

PLUG AND ABANDON ☒

CHANGE PLANS ☐

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☐

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well was formerly the Humble Oil & Refining Co. New Mexico State (E4847) "BA" #1. Forms C-101 and C-128 were filed in June, 1958. Humble staked and drilled the well to 14,585' as a dry hole. 8-5/8" casing was set and cemented. Humble plugged the well December 24, 1958.

A permit was issued by New Mexico Oil Conservation Commission to Guy I. Warren to re-enter and test the 4,200' zone on July 14, 1967. The well was re-entered, top cement plug was drilled out and cast iron bridge plug was set at 4,300'. The zone 4,172' - 4,242' was tested. Form C-103 was filed March 14, 1968.

It is proposed to move in rig on October 3, 1974 to plug and abandon the well. Will place cement plug from 4,242' to 4,100', cut off 8-5/8" casing at approximately 1,000', place cement plug across cut-off section and place cement plug at surface.

33 1/8" 416-450
13 1/4" 1474-300
9 1/8" 5346-800 TOC. 950

hereby certify that the information above is true and complete to the best of my knowledge and belief.

W.W. Watson, TITLE Agent

DATE September 27, 1974

W.A. Gressett, TITLE OIL AND GAS INSPECTOR

DATE SEP 30 1974

DITIONS OF APPROVAL, IF ANY:

Intervals between plugs filled w/ mud