

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 064819
Unit J. F. Heard

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 24, 1951

Well No. 1 is located 1980 ft. from N line and 1980 ft. from W line of sec. 33

SE/4 of NW/4 6-S 9-E -
(1/4 Sec. and Sec. No.) (Range) (Meridian)
Wildcat Lincoln County New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5892 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Abandonment procedure:

1. Ran Schlumberger electric log from 4504-8050' (TD).
2. Ran dipmeter survey.
3. Ran gamma ray and neutron survey from surface to 8050' (TD).
4. Spotted plug #1 on bottom from 7971-8050' w/30 sacks cement.
5. Spotted plug #2 from 4394-16' w/30 sacks cement. Could not feel plug. Respotted plug #2 from 4362-4440'. Found plug.
6. Recovered 1918' of 9 5/8" casing.
7. Spotted following remaining cement plugs: #3, 1910-2013' w/40 sacks cement.
#4, 1430-95' w/51 sacks cement.
#5, surface to 30' w/45 sacks cement

8. Recovered rods and 7" casing in water well
9. Moved rig off location. (10) Cleaned location as well as possible at present.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Unable to completely fill mud and waste pits as pits were not sufficiently dry to
Company STANDARD OIL COMPANY OF TEXAS work.

Address Box 1660

Midland, Texas

By H. W. Mathews

Title Div. Prod. Supt.

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces

Lease No. 064819

Unit J. F. Heard

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 10, 1951

Well No. 1 is located 1980 ft. from N line and 1980 ft. from E line of sec. 33
SE/4, NW/4 6-S 9-E -
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat Lincoln, County New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5892 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Confirming telephone conversation of April 10, granting permission to plug and abandon well with following abandonment procedure:

1. Run Schlumberger electrical log and dipmeter surveys.
2. Run gamma ray and neutron logs.
3. Spot 75' cement plugs at total depth and at shoe of 9 5/8" casing @ 4503'.
4. Recover 9 5/8" casing landed at 4503' with 150 sacks.
5. Spot cement plug between approx. 2065' and 2235' to separate fresh water sands from salt water sands.
6. Spot cement plug at shoe of 13 3/8" casing @ 1446'.
7. Spt cement plug at surface.
8. Pull rods and casing out of water well and release water well to landowner.
9. Move off rig.
10. Clean up location.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company STANDARD OIL COMPANY OF TEXAS

Address Box 1660

Midland, Texas

By H. W. Mathews

Title Div. Prod. Supt.