



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office

Lease No. NM 077195

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT..... X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

....., 19.....

Well No. Federal 1 is located 3,625 ft. from $\left\{ \begin{smallmatrix} NM \\ S \end{smallmatrix} \right\}$ line and 505.72 ft. from $\left\{ \begin{smallmatrix} NE \\ W \end{smallmatrix} \right\}$ line of sec. 30SW $\frac{1}{4}$ NW $\frac{1}{4}$ (Lot 2) 30
($\frac{1}{4}$ Sec. and Sec. No.)6 S.
(Twp.)10 E.
(Range)N.M.P.M.
(Meridian)Wildcat
(Field)Lincoln
(County or Subdivision)New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Total depth of well: 1500 feet

10" surface casing set at 104 feet. Cement circulated.

Well was plugged and abandoned as follows:

1. A 20-sack plug was set at 1100 feet. Cement set 48 hours and tested O.K. when weight was set on it.
2. A 20-sack plug was set at 850 feet. Cement set 48 hours and tested O.K. when weight was set on it.
3. A 20-sack plug was set at 600 feet. Cement set 48 hours and tested O.K. when weight was set on it.
4. A 10-sack plug was set at 500 feet. Cement set 48 hours and tested O.K. when weight was set on it.
5. A 5-foot plug was placed in top of surface casing and dry hole marker installed.
6. Location was restored as nearly as possible to its original condition.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Well will eventually be converted to a water well.

Company Bryce Duggar

Address Box 156

Carrizozo, New Mexico

By *Bryce Duggar*

Title