

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, New Mexico

July 14, 1945

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Stanolind Oil and Gas Company PICACHO UNIT Well No. 1 in NW/4 of NW/4
Company or Operator Lease
of Sec. 10, T. 12-S, R. 18-E, N. M. P. M., Wildcat Field,
Lincoln County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Subject well was drilled with cable tools to total depth of 2843', encountering granite formation without any shows of oil or gas. We propose to plug and abandon in the following manner; Fill the hole with heavy mud to 2650' where a small show of fresh water was encountered, set a 10-sack cement plug at this point and fill hole with mud to 1863' at bottom of 8-5/8 casing cemented with fifty sacks. Recover as much of 8-5/8" as possible (estimated 1650'), then fill hole back to 1171' where 10-3/4 casing was set with twenty-five sacks, place a ten-sack cement plug in bottom of 10-3/4, recover as much as possible (estimated 1050'), leave the fresh water (Gloretta sand) exposed for future use. One joint of 13" casing will be set at surface, cemented and capped to protect water well from surface contamination. Cellar and pits will be leveled off and a four-inch pipe marker will be erected, extending five feet above ground level.

Approved this 12th day of March,
1946-

John E. Miller
COMMISSIONER OF PUBLIC LANDS
Approved MAR 23 1946, 19
except as follows:

Signed Geo. M. Slaughter Owner of Grazing Lease
I hereby accept responsibility of this well
under conditions as stated above.

Dated: July 14 1945.

Stanolind Oil and Gas Company
Company or Operator

By Ralph L. Hendrickson

Position Field Superintendent

Send communications regarding well to

Name Ralph L. Hendrickson

Address Box F, Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By Roy Garbrough
Title _____

