

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

SEP 29 1981

O. C. D.
ARTESIA OFFICE

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
LG-6862

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REFRAC OR TO PLUG BACK TO A DIFFERENT ZONE. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Yates Petroleum Corporation 3. Address of Operator 207 South 4th St., Artesia, NM 88210 4. Location of Well UNIT LETTER D 660 North 660 THE West LINE, SECTION 36 TOWNSHIP 7S RANGE 20E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 4375' GR	7. Unit Agreement Name 8. Farm or Lease Name White Flat "LO" State 9. Well No. 1 10. Field and Pool, or Wildcat Wildcat Granite 12. County Lincoln
--	--

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to plug and abandon as follows:

- 1) Set CIBP @2300' and cap w/35' Class "C" cement
- 2) Cut and pull 5 1/2" casing from approximately 1950'
- 3) Set 100' Class "C" cement plug (min. 35 sx) 50' in and out of 5-1/2" stub
- 4) Set 100' Class "C" cement plug (min. 35 sx) 50' in and out of 9-5/8" casing shoe @620' tag
- 5) Set 25 sacks Class "C" cement surface plug
- 6) Install regulation abandonment marker
- 7) Clean and level location

Verbal approval for plugging procedure was obtained from Mr. Gressett, NMOCD, Artesia, on 9-28-81.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Albert J. Gressett TITLE Engineer DATE 9-29-81

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE OCT 2 1981

CONDITIONS OF APPROVAL, IF ANY:

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG-6862	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.

RECEIVED

APR 24 1981

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation

O. C. B.

ARTESIA OFFICE

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER D 660 North 660
 THE West 36 TOWNSHIP 7S RANGE 20E

7. Unit Agreement Name

8. Farm or Lease Name

White Flat "LO" State

9. Well No.

1

10. Field and Pool, or Wildcat

Wildcat Granite

11. Elevation (Show whether DF, RF, GR, etc.)

4375'

12. County

Lincoln

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
 TEMPORARILY ABANDON ☐
 PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
 CHANGE PLANS ☐

REMEDIAL WORK ☐
 COMMENCE DRILLING OPS. ☐
 CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐
 PLUG AND ABANDONMENT ☐

OTHER ☐ Production Csg, Perforate & Treat

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 5344' - Ran 115 joints of 5-1/2" 14# K-55 ST&C (5069') of casing set at 5069'. Cemented w/450 sx 50/50 Poz, Class C 4% gel, 2/10% Halad-22, 4/10% CFR-2, 3#/sack KCL. PD 10:10 AM. WOC in excess of 12 hours. TD 5344; PBDT 5034'-WIH w/casing gun on wireline & perforated as follows: 3612-3640' w/56 .50" holes (2spf). POOH. WIH w/Guiberson Uni Vi packer on 2-7/8" tubing set packer at 3575' & treated w/750 gallons 15% Spearhead MX acid. TD 5344; PBDT 2530'- WIH & set a CIBP at 3560', dumped 35' of cement on top. WOC. WIH & perforated 5 1/2" casing at 2580' w/2 holes. Broke circulation & cemented thru EZ Retainer set at 2530' w/500 gallons of mud flush & 275 sacks of Class C cement. Ran Temperature Survey & found top of cement at 2050'. WIH w/casing gun on wireline & perforated 2335-43' w/9 .50" holes. POOH. Swabbed. No fluid in hole. Set packer at 2295'. Treated perforations w/1000 gallons Spearhead acid w/ball sealers. Sand Frac'd perforations 2335-43' w/2200 gallons Titan-30, 2000 gallons 15% Spearhead acid, 60000# sand (50000# 20/40 sand & 10000# mesh).

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mr. Anita DoodetteTITLE Engineering SecretaryDATE 4-24-81APPROVED BY Mr. W. WilliamsTITLE OIL AND GAS INSPECTORDATE APR 28 1981

CONDITIONS OF APPROVAL, IF ANY: