

OIL CONSERVATION DIVISION

P. O. BOX 2688

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OCT - 7 1981

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 6862	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER- P&A
1. Name of Operator		
Yates Petroleum Corporation		
2. Address of Operator		
207 South 4th St., Artesia, NM 88210		
3. Location of Well		
UNIT LETTER D	660	FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 36 TOWNSHIP 7S RANGE 20E NMPM.

7. Unit Agreement Name
8. Farm or Lease Name
White Flat "LO" State
9. Well No.
1
10. Field and Pool, or Wildcat
Wildcat Granite
12. County
Lincoln

15. Elevation (Show whether DF, RT, GR, etc.)
4375' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plugged and abandoned well as follows:

- 1) Set CIBP at 2300' and capped w/35' Class C cement.
- 2) Cut casing at 1950', would not come, stuck cutter at 1825'. Cut wireline at 1800'. Attempted to cut casing at 1800' twice, but would not come.
- 3) Set 35 sacks Class C 3% CaCl - 1600-1800'. Tagged plug at 1590'.
- 4) Cut 5-1/2" casing at 750' and pulled.
- 5) Set 75 sacks Class C 3% CaCl cement - 560-800'. Tagged plug at 560'.
- 6) Set 25 sacks Class C cement at surface plug.

Install regulation abandonment marker. Location will be cleaned and levelled.

Verbal approval for plugging procedure obtained from Mr. Grossett, NMOCD, Artesia, 9-28-81.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Quante Goodlett</u>	TITLE <u>Engineering Secretary</u>	DATE <u>10-6-81</u>
APPROVED BY <u>Danell Moore</u>	TITLE <u>Geologist</u>	DATE <u>3/16/88</u>
CONDITIONS OF APPROVAL, IF ANY:		