

WATER CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

MAR 08 1981  
C. C. D.  
SANTA FE, NEW MEXICO

5a. Indicate Type of Lease  
State ☒ Fee ☐  
5. State Oil & Gas Lease No.  
**LG-8525**

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator <b>MESA PETROLEUM CO.</b>	8. Farm or Lease Name <b>CHADWICK State</b>
3. Address of Operator <b>1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701</b>	9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>K</b> <b>1980</b> FEET FROM THE <b>SOUTH</b> LINE AND <b>1980'</b> FEET FROM THE <b>WEST</b> LINE, SECTION <b>2</b> TOWNSHIP <b>2S</b> RANGE <b>15E</b> NMPM.	10. Field and Pool, or Wildcat <b>WILDCAT</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>6011.3' GR</b>	12. County <b>LINCOLN</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 11" hole to 1730' on 3-4-81. Ran 39 jts 8 5/8", 24#, J-55 casing set at 1729'. Cemented with 350 sx LT + 4% CaCl, 100 sx Thixset + 4% CaCl, 350 sx LT + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. Circulated 20 sx to pit. WOC 16 hours. Tested BOP's and casing to 600 psi for 30 minutes - OK. Reduced hole to 7 7/8" and drilled ahead on 3-5-81.

XC: NMOC (6), TLS, HOBBS, MEC, LAND, PARTNERS, FILE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. P. Nathan TITLE REGULATORY COORDINATOR DATE MARCH 6, 1981

For Record Only

APPROVED BY Nathan W. Williams TITLE OIL AND GAS INSPECTOR DATE MAR 11 1981

CONDITIONS OF APPROVAL, IF ANY: