

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

WATER CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 12-1-78

87501
AUG 20 1981

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease

State ☒ Farm ☐

5. State Oil & Gas Lease No.

LG 7545

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator

TERRA OF NEW MEXICO, INC. ✓

Address of Operator

7409 South Alton Court - Suite 210, Englewood, Colorado 80112

Location of Well

UNIT LETTER N, 2452 FEET FROM THE West LINE AND 650 FEET FROM

THE South LINE, SECTION 25 TOWNSHIP 10S RANGE 19E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Riley State

9. Well No.

1

10. Field and Pool, or Wildcat

Wildcat

15. Elevation (Show whether DF, RT, GR, etc.)

4775 GL

12. County

Lincoln

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPER. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☒

OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-22-81 Cement 400' 10 3/4 casing in 14 3/4' open hole using 100 sx Class C & 10% D-53 & 2% Calcium 5# Kolite Per sk. Tail in with 400 sx. Class C & 3% Calcium & 1/2# D-29 per sk. No circulation during cementing WOC 12 hrs Run 1# to tag cement after temp survey 100' fill-up.

6-23-81 Mix 50 sx cement via 1" (Class C & 4% C.C.) tag cement 130' fill up Mix 100 sx Class C & 4% C.C. Tag cement with 1" cement within 42' surface Dump approx. 4 1/2 yards pea gravel in hole Cement to surface via 1" using 50 sx Class C & 4% Calcium chloride Good returns to surface.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature]

TITLE Field Engineer

DATE August 10, 1981

APPROVED BY [Signature]

TITLE OIL AND GAS INSPECTOR

DATE SEP 23 1981

CONDITIONS OF APPROVAL, IF ANY: