

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>RIO PETRO LTD.</u>			Lease <u>NOSKE 12 #</u>		Well # <u>1-Y</u>
Location of Well	Unit <u>0</u>	Section <u>16</u>	Township <u>10S</u>	Range <u>15E</u>	County <u>LINCOLN</u>
Drilling Contractor	<u>YUCCA DRILLING</u>		Type of Equipment <u>ROTARY</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <u>12 1/2"</u>	<u>8 5/8"</u>	<u>24#</u>	<u>NEW</u>	<u>400'</u>	<u>CIRC</u>
<u>7 7/8"</u>	<u>5 1/2"</u>	<u>15.5#</u>	<u>"</u>	<u>1200'</u>	<u>CIRC</u>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 250

Type of Shoe used TYPE M Float collar used INSERT Btm 3 jts welded yes

TD of hole 214 Set 205 Feet of 8 5/8 Inch 24 # Grade J-55

New/used csg. @ 205 with 100 sacks neat cement around shoe
+ 150 sack H.Life additives 1/4# flocc 2% Cell;

Plug down @ 1:00 (AM) (PM) Date 1-16-84

Cement circulated yes fell back No. of Sacks -5-

Cemented by HALLIBURTON Witnessed by Harry Brooks

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: REDIMIXED FROM SURFACE CMT. TOP 30'

TOTAL YDS. USED : 5