

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Artesia, NM 88210

Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to different formations.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	5. LEASE DESIGNATION AND SERIAL NO. NM-39755
2. NAME OF OPERATOR Yates Petroleum Corporation	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1780 FNL & 1980 FEL, Sec. 25-T4S-R14E	8. FARM OR LEASE NAME Boggle ZH Federal
	9. WELL NO. 1
	10. FIELD AND POOL, OR WILDCAT Wildcat
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit G, Sec. 25-4S-14E
14. PERMIT NO.	12. COUNTY OR PARISH Lincoln
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6014' GR	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>	PULL OR ALTER CASING	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	MULTIPLE COMPLETE	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	ABANDON*	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	CHANGE PLANS	<input type="checkbox"/>
(Other)	<input type="checkbox"/>		

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	<input checked="" type="checkbox"/>	REPAIRING WELL	<input type="checkbox"/>
FRACTURE TREATMENT	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
SHOOTING OR ACIDIZING	<input type="checkbox"/>	ABANDONMENT*	<input type="checkbox"/>
(Other)	<input type="checkbox"/>		

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Spudded 14-3/4" hole 11:30 AM 5-1-84. Ran 16 joints of 10-3/4" 40.5# J-55 ST&C casing set 675'. 1-Type "M" notched guide shoe set 675'. Insert float set 642'. Cemented w/400 sacks Pacesetter Lite, 12#/sack Hiseal, 3#/sack Permacheck, 1/2#/sack celloseal, 3% CaCl2. Tailed in w/200 sacks Class "C", 5#/sack Hiseal, 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 3:30 PM 5-3-84. Bumped plug to 600 psi, released pressure and float held okay. WOC. Drilled out 9:30 AM 5-4-84. WOC 18 hours. Nipped up and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED Peter W. Chester TITLE Production Supervisor DATE 5-7-84

(This space for Federal or State office use)

APPROVED BY PETER W. CHESTER TITLE Production Supervisor DATE 5-7-84  
CONDITIONS OF APPROVAL, IF ANY

\*See Instructions on Reverse Side