

95F

RECEIVED BY
MAR 12 1985
O. C. D.
ARTESIA OFFICE

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

LEASE DESIGNATION AND SERIAL NO.
NM 19662

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use APPLICATION FOR PERMIT for such proposals.)

1. WELL NO. WELL OTHER

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

2. NAME OF OPERATOR
Dalton Kincheloe

7. UNIT AGREEMENT NAME

3. ADDRESS OF OPERATOR
859 Petroleum Bldg, Roswell, NM 88201

8. FARM OR LEASE NAME
Arnold Federal

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Wildcat - *Yes*

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 20 T6S R13E

890' FNL & 890' FEL of Section 20, T6S, R13E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, GR, etc.)
6797' GR

12. COUNTY OR PARISH
Lincoln

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)
PULL OR ALTER CASING
MULTIPLE COMPLETION
ABANDON*
CHANGE PLANS

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other) Move in Rotary Rig & set csg
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
REPAIRING WELL
ALTERING CASING
ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

See previous reports: Drilled to 1,006' with cable tools. Ran 14 jts (543') of 8-5/8" 24# casing, set at 543' - did not cement.

2/21/85 Moved off cable rig. Moved in and Rigged Up Artesia Fishing Tool #1 (rotary rig). Pulled 8-5/8" casing, reamed hole to TD 1006', drilled 12 1/4" hole to 1200', Ran 30 jts. (1205") of 8-5/8" 24# casing, set and cemented @ 1194' with 500 sacks Halliburton Lite with 1/4# floseal and 2% CaCl per sk, followed by 200 sacks Class C with 2% CaCl. Plug Down @ 2:15 a.m. 2/28/85. Did not circulate. Ran Temperature Survey, Top of cement @ 575'. One inched at 234' with 200 sacks Class C cement with 2% CaCl. Circulated 10 sacks to surface. Plug down @ 11:00 a.m. 2/28/85. WOC 12 hrs.

MAR 6 1985

18. I hereby certify that the foregoing is true and correct

SIGNED *Jackie Midkiff*

TITLE Jackie Midkiff/Prod. Clrk.

DATE 3/1/85

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
PETER W. CHESTER
MAR 8 1985
BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side