		THE GLASSICS OF THE STATE OF TH	5. LEASE DESIGNATION AND SERIAL NO.
CUNDRY NO	TICES AND REPOR JOALIS to drill or to deepen or CATION FOR PERMIT—" for		NM 37128 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL Q. C. CD. X OTHER			7. UNIT AGREEMENT NAME
- CALE DE CARDICE			8. FARM OR LEASE NAME Chisum "AAW" Federal
Yates Petronoum Corporation 3. ADDRESS OF OPERATOR			9. WHILL NO.
207 South 4th St., Artesia, NM 88210 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*			1 10. FIELD AND POOL, OR WILDCAT
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.) See also space 17 below.) At surface			Wildcat - //
1980 FNL & 1980 FEL, Sec. 27-T2S-R19E			11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA
			Unit G, Sec. 27-2S-19E
14. PERMIT NO.	15. BLEVATIONS (Show whe	• • • •	12. COUNTY OR PARISH 13. STATE
	4954'	GR	Lincoln NM
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INT	ENTION TO:	SUBSEC	QUENT REPORT OF:
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE	MULTIPLE COMPLETE ABANDON®	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING	X REPAIRING WELL ALTERING CASING ABANDONMENT®
(Other)	CHANGE PLANS	(Other)	s of multiple completion on Well pletion Report and Log form.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *			
Ran 10 joints 13-3/8" 5 420'. Insert float set celloseal, 2#/sx Permach pressive strength of ce 800 psi, released press culate. WOC 8 hrs. R cement 140'. Spotted 2 Ran 1". Tagged cement 1-1/2 hrs. Ran 1". Ta 1-7-85. WOC 1-1/2 hrs. PD 7:45 AM 1-7-85. Cem 22 hrs and 15 minutes. 12-1/4". Drilled plug a	4.5# J-55 ST&C cas 378'. Cemented w eck and 3% CaCl2. ment - 1250 psi in ure and float did an Temperature Sur 5 sx Class C w/4% 120'. Spotted 25 gged cement 120'. Ran 1". Tagged ent circulated 5 s NU and tested to nd resumed drillin	CaCl2. PD 3:00 AM 1-7-8 sx Class C w/4% CaCl2. Spotted 25 sx Class C w cement 90'. Spotted 40 acks. WOC. Drilled out 1500 psi for 30 minutes;	Notched guide shoe set w/15#/sx Hiseal, 1#/sx s C w/2% CaCl2. Com85. Bumped plug to n. Cement did not cir- ent 150'. Ran 1". Tagged 5. WOC 1-1/2 hrs. PD 4:30 AM 1-7-85. WOC 1-4% CaCl2. PD 6:00 AM sx Class C 4% CaCl2.
18. a hereby certify that the foregoin	*	Production Supervisor	DATE 1-8-85
		-	
APPROVED BY CONDITIONS OF APPROVAL.	ENED FOR HEALTH	3	DATE
	AN 15 1985		
	· · · · · · · · · · · · · · · · · · ·	uctions on Reverse Side	