

NUMBER OF COPIES RECEIVED		4
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
TRANSPORTER	OIL	
	GAS	
PRODUCTION OFFICE		
OPERATOR		2

(Form C-102)
(Revised 7/1/62)

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be furnished to the Bureau on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	XX	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

January 13, 1964

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Skelly Oil Company **New Mexico "C"** Well No. **1-A** in **"00"**
(Company or Operator)
SW **SE** **19** **28-S** **54"** **Wildcat** **RECEIVED** (Unit)
(40-acre Subdivision) 1/4 of Sec. T. R. NMPM, Pool
Luna County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was drilled to a total depth of 9422' with no commercial quantities of oil or gas encountered in any zone. Well will be plugged and abandoned in the following manner:

1. Spot cement plugs through open ended drill pipe as follows:
9422-9522' - 50 sacks of cement
7600-7645' - 75 sacks of cement
5000-4900' - 100 sacks of cement
1175-1075' - 100 sacks of cement
2. 25 sacks of cement in top of 13-3/8" OD casing and install 4" pipe marker.
3. All intervals not cemented will be filled with heavy mud laden fluid.

Verbal approval to plug and abandon this well was given to Mr. Jerry I. Moritz by Mr. M. L. Armstrong on January 13, 1964.

Approved..... **JAN 16 1964** , 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By **M. L. Armstrong**

Title.....

Skelly Oil Company

(ORIGINAL)
By..... **(SIGNED) M. E. Aab**

Position..... **Dist. Superintendent**

Send Communications regarding well to:

Name..... **Skelly Oil Company**

Address..... **Box 730 - Hobbs, New Mexico**