

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

FEB 7 1973

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-6592

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Walden S. Guest & I. J. Wolfson	7. Unit Agreement Name
3. Address of Operator c/o Oil Reports & Gas Services, Inc., Box 763, Hobbs, N. M. 88240	8. Farm or Lease Name Diana
4. Location of Well UNIT LETTER F , 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 16 TOWNSHIP 23 S RANGE 11 W NMPM.	9. Well No. 1
	10. Field and Pool, or Wildcat Wildest
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Luna

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 8:00 AM 12/16/72. Set 1 joint 13 3/8" 48# H-40 conductor casing at 20' with 5 sacks cement. Job complete 12/16/72.

Cemented 8 5/8" 28# J-55 casing @ 2017' with 450 sacks Halliburton Lite cement and 200 sacks class "C" 2% calcium chloride. Cement circulated. Plug down 12:00 Noon 1/5/73. WOC 18 hours, pressure tested casing with 1200# for 30 minutes, test O.K. Drilled out plug after 20 hours with 7 7/8" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Wanda Heller* TITLE **Agent** DATE **2/6/73**

APPROVED BY *For Record Only* TITLE **OIL AND GAS INSPECTOR** DATE **MAR 8 1973**

CONDITIONS OF APPROVAL, IF ANY: