STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

AUT AND IN LEARNING B.		, v.c
DISTRIBUTION		
BANTA FE	10	
FILE	V	-
U.S.G.S.		Ĺ
LAND OFFICE		
CPERATOR	7.7	

did not circulate.

OIL CONSERVATION DIVISION P. O. BOX 2088 SANTA FE, NEWMARXI do 1983 01

O. C. D. ARTESIA, OFFICE

F	0	r	ា		C	-	1	J)					
R	¢	٧	1	S	e	đ		1	ŋ	-	1	-	7	5

For XX

Sa. Indicate Type of Leise

5. State Cil & Gas Lease No.

State []

SUNDRY NOTICES AND REPORTS ON WELLS	
1. OIL XX GAS WELL OTHER-	7, Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
SEVILLE-TRIDENT CORPORATION	Hurt Ranch
3. Address of Operator	9. Well No.
Post Office Box 532, Midland, Texas 79702	1
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER C 660 FEET FROM THE NORTH LINE AND 1980 FEET FROM	Wildcat
THE West LINE, SECTION 8 TOWNSHIP 24-S RANGE 10-W NAPH.	
15. Elevation (Show whether DF, RT, GR, etc.) 4407 G.L.	12. County Luna
Check Appropriate Box To Indicate Nature of Notice, Report or Oth NOTICE OF INTENTION TO: SUBSEQUENT	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK TEMPORARILY ABANDON COMMENCE DRILLING OPNS. PULL OR ALTER CASING CASING TEST AND CEMENT JOB XX	ALTERING CASING PLUG AND ABANDONMENT
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.	estimated date of starting any proposed
Drilled 12 1/4" hole to 1940' K.B.	
Ran 46 jts 9 5/8", 36#/ft., J-55, ST&C casing; set at 1940' with DV to	ool at 940'.
Cemented first stage with 430 sacks Class "H" neat and 400 sacks Class Plug down at 3:15 PM, February 9, 1983. Opened DV tool and circulated circulated back 200 sacks cement.	

WOC five hours. Ran 1" pipe in 9 5/8" - 12 1/4" annulus to top of cement at 148'. Cemented through 1" with 110 sacks Class "H" with 3% CaCl₂. Circulated 10 sacks to surface. Cementing completed at 6:30 AM, February 10, 1983.

Cemented second stage with 700 sacks Class "H" with 7#/sack gilsonite and 200 sacks Class "H" with 7#/sack gilsonite and 2% CaCl2. Plug down at 11:00 PM, February 9, 1983. Cement

WOC twenty-four hours. Pressured casing and BOP's to 2000 psi for thirty minutes with no

	15 ANY	TITLE	Original Sig Leslie A. Cl Supervisor E	ements	DAT	MAR 0 2 1983
	alariation above in true and			ledge and belief.	DAT	. <u>28 February</u> 1983
pressure loss. minutes with no	Drilled out DV t pressure loss.	cool. Tested	DV tool	and casing to	2000 psi	for thirty