

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
P.O. Box 2088 RECEIVED
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

MAY 23 '89

WELL API NO.

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Santa Maria DB R&R

8. Well No.

#1

9. Pool name or Wildcat

Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS O. C. D.
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR RE-LEASE A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☒

OTHER

2. Name of Operator

XTER, INC

3. Address of Operator

Box 912-A, RR #2, Deming, NM 88030

4. Well Location

Unit Letter N 658, 76 Feet From The South Line and 1929.23 Feet From The West Line

Section 19 Township 21S Range 10W NMPM Luna County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4277' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

A 7 inch surface casing was set to a depth of 644 feet. Western Company pumped 385 sacks of class c cement and two percent calcium chloride on March 1, 1989. Cement was circulated to the top and observed by a State Oil Conservation employee. On March 3, 1989, a pressure test was conducted to 630 pounds for 33 minutes.

On May 2 plugging operations began. Forty eight sacks of mud gel was mixed in the mud pit and then pumped into the well until the gel circulated to the top. Twenty five sacks of class c cement was batch mixed and then pumped through a 2 3/8 inch tubing to 1,000 feet. The tubing was pulled up to 675 feet where 35 sacks of cement were pumped. On May 3 tubing was put into the hole to test the plug, and found the top to be 635 feet. Eleven sacks of cement were set at 635 feet to make a 100 foot plug. Ten sacks of cement were pumped to the 60 foot level for the surface plug.

Erected dry hole marker. Will clean site, and notify NMOCO for final inspection

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ralph Swarthout

TITLE Pres.

DATE 5-5-89

TYPE OR PRINT NAME: RALPH SWARTHOUT

TELEPHONE NO. 546-0225

(This space for State Use)

Original Signed By
Mike Williams

APPROVED BY _____ TITLE _____

DATE MAY 23 1989

CONDITIONS OF APPROVAL, IF ANY: