

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

El Paso, Texas

February 20, 1942.

Place

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

R. H. Ernest

- Located Land Company

Well No. 1 in the

Southeast Corner

of Sec.

20

T. 25 S

R. 7 E

N. M. P. M.,

(Wildcat well)

Field,

Otero

County.

The dates of this work were as follows:

February 1st to February 19th

Notice of intention to do the work was (was not) submitted on Form C-102 on

January 27

19 42

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Filled with shale mud to 2695 feet and bridged at 2695 feet. Placed about 10 feet of rock, etc. on bridge and dumped 3 sacks of cement with bailer. Pulled casing and filled with shale mud to about 740 feet. Bridged and filled with rock, etc. on bridge to 731 feet. Cemented with 12 sacks of cement, dumping cement with bailer. The 15 1/2 inch casing was originally set at 726 feet. On 18th filled 15 1/2" pipe with water to within 40 feet of top and found pipe tight. Shot with 1 1/2 quarts Glycerine from 457 to 461 to make water well in sand 455 to 465.

Witnessed by Walter Morris Driller
Name Company Title

Subscribed and sworn before me this

20th

day of

February

19 42

I hereby swear or affirm that the information given above is true and correct.

Name

Owner

Position

Representing

Paso del Norte Hotel, El Paso, Texas.

My commission expires

5/31/43

Address

Remarks:

Left in Hole. About 95 ft. 20" Casing and 718 ft. 15 1/2" Casing. Water level of Fresh Water 365 ft. from surface.

Rog. Yarbrough
Name
OIL & GAS INSPECTOR
Title

