



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Las CrucesLease No. 069863-A

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<input type="checkbox"/>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

~~El Paso~~ Trigg-Federal No. 1

November 17, 19 51

Well No. 1 is located 1980 ft. from N line and 1980 ft. from W line of sec. 18
NW/4, 18 26 S 11 E NMPL
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat Otero New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5301 ft.* *This ground level elevation.
Derrick floor elevation will
be reported when obtained.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is intended to drill a well in search for oil or gas at the above location with rotary tools to a total depth of approximately 5000' or to the El Paso Line. All casing will be cemented in accordance with approved methods of the U. S. Geological Survey and any other special requirements will be complied with.

The following drilling program will be followed: 13-3/8" OD 54.5#/ft. casing will be set at 700' or such depth that may be required to protect shallow surface beds. This casing will be cemented with 650 sacks or an amount sufficient to cause cement to rise to the surface outside the casing. An 8-3/4" hole will be drilled to approximately 500' and all formations bearing shows of oil or gas will be tested. If a completion is attempted the oil string will consist of 7" OD 23#/ft. casing cemented with approximately 400 sacks.

Approval to produce this well upon completion is also requested.
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SEABOARD OIL COMPANYAddress Box 352Midland, TexasBy A. G. Walsh
A. G. Walsh
Title Engineer