

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-8808

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-

7. UNIT AGREEMENT NAME

-

8. FARM OR LEASE NAME

Federal (USA) "G"

9. WELL NO.

1

10. FIELD AND FLOW OR MUDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33, T-18-S, R-8-E

12. COUNTY OR PARISH

Otero

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

TEXACO Inc.

3. ADDRESS OF OPERATOR

P. O. Box 728 - Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1552' FNL, 1934' FEL, Section 33, T-18-S, R-8-#

14. PERMIT NO.

Regular

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4186' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Plugback & Perforate

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Total Depth 7660'

Plug back total depth 5900'

7-5/8" OD 26.4# casing set at 5975'

The following work has been completed on subject well:

1. Spot 25 sx Class C w/HR-7 from 7400' to 7500'. (100').
Spot 30 sx Class C w/HR-7 from 7000' to 7150'. (150').
Spot 25 sx Class C w/HR-7 from 5925' to 6025'. (50' below 7-5/8" casing shoe and 50' above).
2. Set cast iron bridge plug at 5900'.
3. Perforate 7-5/8" OD casing w/2 JSPF from 5835' to 5854' and tested water.
4. Spotted 50 sx Class C w/1% Halad-9 w/1/4# flocele/sx and 75 sx Class C w/1% Halad-9 w/1/4# flocele and 5# gilsonite/sx across perforations 5835' to 5854'. Tested to 150#. Tested OK.

RECEIVED
SEP - 8 1970
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Assistant District Superintendent

DATE September 4, 1970

(This space for Federal or State office use)

APPROVED BY

TITLE

DISTRICT ENGINEER

DATE

SEP 8 1970

CONDITIONS OF APPROVAL, IF ANY: