Form	9-331
May	1963)

instructions on []

Form approved. Pudget Bureau No. 5. LEASE DESIGNATION AND SERIAL NO

DEPARTMENT OF THE INTERIOR verse side)

GEOLOGICAL SURVEY

	<u>NM-8</u>	3808			
TE		ATTOMMEN	ΩĐ	CDIDE	MAN

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.)

 $_{\rm WELL}^{\rm GAS}$ WELL X NAME OF OPERATOR

TEXACO Inc. 3. ADDRESS OF OPERATOR

P.O. BOX 728 - HOBBS, NEW MEXICO

OTHER

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)

At surface

1552' FNL, 1934' FEL, SECTION 33, T-18-S, R-8-E

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) REGULAR 4186' GR

10. FIELD AND POOL, OF WILDCAT 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

FEDERAL (USA) 'G'

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

SEC. 33, T-18-S, R-8-E

12. COUNTY OR PARISH | 13. STATE **OTERO NEW MEXICO**

16.

(Other)

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: TEST WATER SHUT-OFF PULL OR ALTER CASING FRACTURE TREAT MULTIPLE COMPLETE SHOOT OR ACIDIZE ABANDON REPAIR WELL CHANGE PLANS (Other)

SUBSEQUENT REPORT OF: REPAIRING WELL WATER SHUT-OFF ALTERING CASING FRACTURE TREATMENT ABANDONMENT* SHOOTING OR ACIDIZING (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

The following work has been completed on subject well:

- Shot off and pulled 7-5/8" casing at 4400'.
- Spot 50 sx Class C cement plug across 7-5/8" stub, 4350-4450'.
- 3. Spot 50 sx Class C cement plug in openhole from 3200'-3300'.
- Spot 50 sx Class C cement plug across 10-3/4" casing seat, 1850'-1950'. 4.
- Spot 25 sx Class C cement plug at surface.
- Installed 4" marker extending 4' above ground level. 6.
- Cleaned location. Well plugged and abandoned September 4, 1970.

RECEIVED

SEP-9 1970

SEP-9 1970

J. S. BECLUGGERA MENT

		W
18. I hereby certify that the foregoing a true and correct	Assistant	
SIGNED TITL	District Superintendent	DATE September 8, 1970
· (This space for Federal or State office use)	DISTRICT ENGINEER	APR 2 5 1972
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	Æ	APR 2 7 1972